

Data sheet

020UL

Corpo per lampada spia



Features

Range	020 Comando e Segnalazione SM2 Ø 22
Product	Accessori Ø 22
Type	Corpo lampade spia
Item code	020UL
Description	Corpo per lampada spia
Colour	
Weight - gr	6,000
Custom tariff no.	85365080
GTIN	8052878027247

Technical data

Approvals	CE, UL, CSA, EAC
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-40° ÷ +70°C
Protection degree	IP66 - IP69K (IEC-EN60529 - DIN40050)
Protection against impact	IK03 (IEC-EN62262)
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Material	PA Polyamide
Lens material	PC Polycarbonate
Locking ring material	PA Polyamide
Fixing diameter	22.5mm - Thickness 1÷6mm
Tightening torque	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
Modular pilot light	Must be completed with bulb holder-power supply
Overvoltage category	Class II (IEC-EN61140)
Warranty period	18 months

Data sheet

020UL

Corpo per lampada spia

Technical drawings

