

## Data sheet

### 020ULR

Lampada spia modulare, rossa



## Features

|                   |                                     |
|-------------------|-------------------------------------|
| Range             | 020 Comando e Segnalazione SM2 Ø 22 |
| Product           | Lampade spia Ø 22                   |
| Type              | Modulari                            |
| Item code         | 020ULR                              |
| Description       | Lampada spia modulare, rossa        |
| Colour            | Rosso                               |
| Weight - gr       | 9,000                               |
| Custom tariff no. | 85365080                            |
| GTIN              | 8052878027452                       |

## Technical data

|                           |                                                  |
|---------------------------|--------------------------------------------------|
| Approvals                 | CE, UL, CSA, EAC                                 |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2, CEI EN 61373                 |
| Operating temperatures    | -40° ÷ +70°C                                     |
| Protection degree         | IP66 - IP69K (IEC-EN60529 - DIN40050)            |
| Protection against impact | IK03 (IEC-EN62262)                               |
| Shock resistance          | 30g duration=18ms (EN-IEC 60068-2-27)            |
| Shock resistance          | 50g duration=11ms (EN-IEC 60068-2-27)            |
| Vibration resistance      | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| Material                  | PA Polyamide                                     |
| Lens material             | PC Polycarbonate                                 |
| Locking ring material     | PA Polyamide                                     |
| Fixing diameter           | 22.5mm - Thickness 1÷6mm                         |
| Tightening torque         | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in)                       |
| Modular pilot light       | Must be completed with bulb holder-power supply  |
| Overvoltage category      | Class II (IEC-EN61140)                           |
| Warranty period           | 18 months                                        |

## Data sheet

020ULR

Lampada spia modulare, rossa

## Technical drawings

