

Data sheet

030LFIBL

Lampada spia, filo pannello, blu



Features

Range	032 Comando e Segnalazione - Filo Pannello SM2 Ø 30
Product	Lampade spia Ø 30
Type	Lampade spia
Item code	030LFIBL
Description	Lampada spia, filo pannello, blu
Colour	Blu
Weight - gr	35,000
Custom tariff no.	85365080
GTIN	8052878028886

Technical data

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-25° ÷ +65° C
Protection degree	IP65 (IEC-EN60529)
Protection against impact	IK04 (IEC-EN62262)
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
External bezel material	Anodized aluminum
Lens material	PC Polycarbonate
Locking ring material	ZAMAK zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Front panel	Tamper proof lens
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Modular pilot light	Must be completed with bulb holder-power supply
Overvoltage category	Class I (IEC-EN61140)
Warranty period	18 months

Data sheet

030LFIBL

Lampada spia, filo pannello, blu

Technical drawings

