

Data sheet

030PFAFMR

Pulsante a fungo Ø 40, filo pannello, momentaneo, rosso



Features

Range	032 Comando e Segnalazione - Filo Pannello SM2 Ø 30
Product	Pulsanti a fungo non luminosi Ø 30
Type	Fungo Ø 40
Item code	030PFAFMR
Description	Pulsante a fungo Ø 40, filo pannello, momentaneo, rosso
Colour	Rosso
Weight - gr	50,000
Custom tariff no.	85365080
GTIN	8052878029876

Technical data

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-25° ÷ +65° C
Protection degree	IP65 (IEC-EN60529)
Protection against impact	IK04 (IEC-EN62262)
Mechanical durability	3.000.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 6 blocks (3+3)
Button/mushroom material (illuminated type)	PC Polycarbonate
Button or knob material	PA Polyamide
External bezel material	Anodized aluminum
Locking ring material	ZAMAK zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	Spring return
Overvoltage category	Class I (IEC-EN61140)
Warranty period	18 months

030PFAFMR

