

## Data sheet

### 030PFLIG

Pulsante luminoso, filo pannello, momentaneo, giallo



## Features

|                   |                                                      |
|-------------------|------------------------------------------------------|
| Range             | 032 Comando e Segnalazione - Filo Pannello SM2 Ø 30  |
| Product           | Pulsanti luminosi Ø 30                               |
| Type              | Con guardia                                          |
| Item code         | 030PFLIG                                             |
| Description       | Pulsante luminoso, filo pannello, momentaneo, giallo |
| Colour            | Giallo                                               |
| Weight - gr       | 35,000                                               |
| Custom tariff no. | 85365080                                             |
| GTIN              | 8052878030728                                        |

## Technical data

|                                             |                                                  |
|---------------------------------------------|--------------------------------------------------|
| Approvals                                   | CE, UL, CSA                                      |
| Compliance with standards                   | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards                   | UNI CEI EN 45545-2, CEI EN 61373                 |
| Operating temperatures                      | -25° ÷ +65° C                                    |
| Protection degree                           | IP65 (IEC-EN60529)                               |
| Protection against impact                   | IK04 (IEC-EN62262)                               |
| Mechanical durability                       | 3.000.000 Operations                             |
| Shock resistance                            | 30g duration=18ms (EN-IEC 60068-2-27)            |
| Shock resistance                            | 50g duration=11ms (EN-IEC 60068-2-27)            |
| Vibration resistance                        | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| Contact blocks configuration                | Max no. 6 blocks (3+3)                           |
| Button/mushroom material (illuminated type) | PC Polycarbonate                                 |
| Button or knob material                     | PA Polyamide                                     |
| External bezel material                     | Anodized aluminum                                |
| Locking ring material                       | ZAMAK zinc alloy                                 |
| Fixing diameter                             | 30.5mm - Thickness 1÷6mm                         |
| Tightening torque                           | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| Actuation type                              | Spring return                                    |
| Overvoltage category                        | Class I (IEC-EN61140)                            |
| Warranty period                             | 18 months                                        |

## Data sheet

### 030PFLIG

Pulsante luminoso, filo pannello, momentaneo, giallo

## Technical drawings

