

## Data sheet

### 030PPFLIV

Pulsante luminoso , filo pannello, stabile, verde



## Features

|                   |                                                     |
|-------------------|-----------------------------------------------------|
| Range             | 032 Comando e Segnalazione - Filo Pannello SM2 Ø 30 |
| Product           | Pulsanti luminosi Ø 30                              |
| Type              | Con guardia                                         |
| Item code         | 030PPFLIV                                           |
| Description       | Pulsante luminoso , filo pannello, stabile, verde   |
| Colour            | Verde                                               |
| Weight - gr       | 35,000                                              |
| Custom tariff no. | 85365080                                            |
| GTIN              | 8052878032234                                       |

## Technical data

|                              |                                                  |
|------------------------------|--------------------------------------------------|
| Approvals                    | CE, UL, CSA                                      |
| Compliance with standards    | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards    | UNI CEI EN 45545-2, CEI EN 61373                 |
| Operating temperatures       | -25° ÷ +65° C                                    |
| Protection degree            | IP65 (IEC-EN60529)                               |
| Protection against impact    | IK04 (IEC-EN62262)                               |
| Mechanical durability        | 500.000 Operations                               |
| Shock resistance             | 30g duration=18ms (EN-IEC 60068-2-27)            |
| Shock resistance             | 50g duration=11ms (EN-IEC 60068-2-27)            |
| Vibration resistance         | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| Contact blocks configuration | Max no. 4 blocks (2+2)                           |
| Button or knob material      | PA Polyamide                                     |
| External bezel material      | Anodized aluminum                                |
| Locking ring material        | ZAMAK zinc alloy                                 |
| Fixing diameter              | 30.5mm - Thickness 1÷6mm                         |
| Tightening torque            | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| Actuation type               | Push-Push (maintained position)                  |
| Overvoltage category         | Class I (IEC-EN61140)                            |
| Warranty period              | 18 months                                        |

## Data sheet

030PPFLIV

Pulsante luminoso , filo pannello, stabile, verde

## Technical drawings

