

Data sheet

030RSMNO2F1

Selettore a manopola, nero, 3 posizioni, Cam O, 2 N.O.+2 N.C.



Features

Range	030 Comando e Segnalazione EL-SG Ø 30
Product	Selettori a manopola non luminosi Ø 30
Type	3 posizioni
Item code	030RSMNO2F1
Description	Selettore a manopola, nero, 3 posizioni, Cam O, 2 N.O.+2 N.C.
Colour	Nero
Weight - gr	117,000
Custom tariff no.	85365080
GTIN	8052878035136

Technical data

Approvals	CE, UL, CSA, EAC
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	1.000.000 Operations
Housing material	PA Polyamide
Knob or lever material	PC Polycarbonate
External bezel material	Chromed zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Overvoltage category	Class II (IEC-EN61140)
Contact block	Included
Contact block characteristics	See technical features of 030FA - 030FC - 030F1
Warranty period	18 months

Data sheet

030RSMNO2F1

Selettore a manopola, nero, 3 posizioni,Cam O, 2 N.O.+2
N.C.



Technical drawings

