

Data sheet

030SFPLOGC

Selettore luminoso a manopola, giallo, filo pannello, 3 posizioni, Cam O, ritorno al centro





Features

Range	032 Comando e Segnalazione - Filo Pannello SM2 Ø 30
Product	Selettori a manopola luminosi Ø 30
Type	3 posizioni
Item code	030SFPLOGC
Description	Selettore luminoso a manopola, giallo, filo pannello, 3 posizioni, Cam O, ritorno al centro
Colour	Giallo
Weight - gr	36,000
Custom tariff no.	85365080
GTIN	8052878037550


Technical data

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Protection against impact	IK04 (IEC-EN62262)
Mechanical durability	1.000.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 4 blocks (2+2)
Knob or lever material	PC Polycarbonate
External bezel material	Anodized aluminum
Locking ring material	ZAMAK zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Overvoltage category	Class I (IEC-EN61140)
Warranty period	18 months

Technical drawings



CAM O



020E10
020E10
020PD9

