


Data sheet

030SMNV2F1

Selettore a manopola, nero, 5 posizioni, Cam V, 2 N.O.+2 N.C.



Features

Range	030 Comando e Segnalazione EL-SG Ø 30
Product	Selettori a manopola non luminosi Ø 30
Type	5 posizioni
Item code	030SMNV2F1
Description	Selettore a manopola, nero, 5 posizioni, Cam V, 2 N.O.+2 N.C.
Colour	Nero
Weight - gr	132,000
Custom tariff no.	85365080
GTIN	8052878038809

Technical data

Approvals	CE, UL-CSA (only 030F1-030FA-030FC-030FAA-030FCR)
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	1.000.000 Operations
Housing material	PA Polyamide
Knob or lever material	PC Polycarbonate
External bezel material	Chromed zinc alloy
Housing material	PA Polyamide + chrome
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Overvoltage category	Class II (IEC-EN61140)
Contact block	Included
Contact block characteristics	See technical features of 030FA - 030FC - 030F1
Warranty period	18 months

Data sheet

030SMNV2F1

Selettore a manopola, nero, 5 posizioni,Cam V, 2 N.O.+2
N.C.



Technical drawings

