



Features

Range	050 Segnalazione ed Illuminazione Quadri Elettrici
Product	Colonne luminose componibili
Type	Tubi di prolunga
Item code	050TA
Description	Anello di fissaggio per colonna luminosa
Colour	
Weight - gr	6,000
Custom tariff no.	85365080
GTIN	8052878049775

Technical data

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-25 ° ÷ +65 °C
Protection degree	IP44 (IEC-EN60529)
Protection against impact	IK07 (IEC-EN62262)
Housing material	PC Polycarbonate
Combustion behaviour	V0 (UL94)
Terminal screw	Tightening torque 0.8÷1 Nm (IEC-EN60947-1)
Terminal screw head shape	Combined:cross Phillips2 or slotted flat D.5mm max
Terminal screw material	Zinc plated steel
Bulb type	Ba15d 250V AC-DC 10W max (not included)
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Overvoltage category	Class II (IEC-EN61140)
Signalling type	Steady - Up to 5 modules
Assembly style	050TBA + 050TM + 050TA or 050TP
Warranty period	18 months

Data sheet

050TA

Anello di fissaggio per colonna luminosa

Technical drawings

Ø25

