

Data sheet

060APATLRCL

Pulsante di emergenza a palmo, luminoso, ad aggancio
tasto bombato rosso, custodia luminosa



Features

Range	060 Dispositivi di Comando di Sicurezza
Product	Pulsanti di emergenza a palmo, tasto e custodia luminosi
Type	Pulsante a palmo, ad aggancio, tasto bombato
Item code	060APATLRCL
Description	Pulsante di emergenza a palmo, luminoso, ad aggancio tasto bombato rosso, custodia luminosa
Colour	Rosso
Weight - gr	394,000
Custom tariff no.	85365080
GTIN	8052878050146

Technical data

Approvals	CE, UL, CSA
Compliance with standards	UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1
Compliance with standards	UNI CEI EN 45545-2
Operating temperatures	-30° ÷ +120°C
Protection degree	IP66 - IP69K (IEC-EN60529 - DIN40050)
Protection against impact	IK08 (IEC-EN62262)
Mechanical durability	3.000.000 Operations
Button/mushroom material (illuminated type)	PC Polycarbonate
Housing material	PA Polyamide V0 (UL94)
Gasket material	Cork rubber
Screw material	Stainless steel AISI 304
Cover screws tightening torque	1 ÷ 2.5Nm (8.8÷22.1 Lb-in)
Terminal screw	Tightening torque 0.8÷1 Nm (IEC-EN60947-1)
Terminal screw head shape	Combined: cross Phillips2 or slotted flat D.5mm max
Terminal screw material	Zinc plated steel
Terminal screw connections	min 1x0.5mm ² (20AWG) - max 2x2.5mm ² (14AWG)
Actuation possibilities	By hand, elbow or foot
For illuminated version	LED circuit 24V AC-DC 25mA
LED connections for illuminated version	min 1x0.25mm ² (22AWG)- max 1x1mm ² (17AWG)
Contact material	Ag 1000/1000

Data sheet

060APATLRCL

Pulsante di emergenza a palmo, luminoso, ad aggancio
tasto bombato rosso, custodia luminosa

Contact movement	Slow action contact
Contacts	Self cleaning by pads creeping
NC Contact	Positive opening function (EN-IEC 60947-5-1 ann.K)
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Rated thermal current	Ith 10A (IEC-EN60947-1)
Electrical ratings	AC15-DC13 (IEC-EN60947-5-1) - A600-P300 (UL 508)
AC Performances	AC 24V-10A, 120V-6A, 240V-3A, 600V-1.2A
DC Performances	DC 24V-5A, 120V-1.1A, 240V-0.55A
Contact block	1NO+1NC Included
Halogen-free	yes
Warranty period	18 months

Data sheet

060APATLRCL

Pulsante di emergenza a palmo, luminoso, ad aggancio
tasto bombato rosso, custodia luminosa

Technical drawings

