

Data sheet

060PMGR

Scatola pulsantiera grigia, in resina termoplastica con piastra alluminio senza fori



Features

Range	060 Dispositivi di Comando di Sicurezza
Product	Pulsantiera mobile
Type	Scatola pulsantiera in resina termoplastica
Item code	060PMGR
Description	Scatola pulsantiera grigia, in resina termoplastica con piastra alluminio senza fori
Colour	Grigio RAL 7016
Weight - gr	680,000
Custom tariff no.	85381000
GTIN	8052878051679

Technical data

Approvals	CE
Compliance with standards	IEC-EN60529
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-25° ÷ +65° C
Protection degree	IP66 - IP69K (IEC-EN60529 - DIN40050)
Protection against impact	IK07 (IEC-EN62262)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	EPDM Foam + adhesive
Screw material	Stainless steel AISI 304
Front plate material	Anodized aluminium - Thickness 2mm
Front plate	Included - Undrilled for customized layout
Tightening torque	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
Cable entry	M20x1,5
Overvoltage category	Class I (IEC-EN61140)
Handle with left / right knockouts	For 016P3Pxxx 3 position enabling safety switch
Warranty period	18 months

Data sheet

060PMGR

Scatola pulsantiera grigia, in resina termoplastica con piastra alluminio senza fori

Technical drawings

