

## Data sheet

### 080C0918-8P5L

Scatola pulsantiera in polycarbonato 94x180x81, 5 fori Ø 22



## Features

|                   |                                                             |
|-------------------|-------------------------------------------------------------|
| Range             | 080 Scatole e Cassette Pulsantiere in Termoplastico         |
| Product           | Scatole pulsantiere 94x180 mm                               |
| Type              | Coperchio con 5 fori Ø 22                                   |
| Item code         | 080C0918-8P5L                                               |
| Description       | Scatola pulsantiera in polycarbonato 94x180x81, 5 fori Ø 22 |
| Colour            | Grigio RAL 7035                                             |
| Weight - gr       | 304,000                                                     |
| Custom tariff no. | 85381000                                                    |
| Material          | Polycarbonato                                               |
| GTIN              | 8052878055318                                               |

## Technical data

|                                |                                                    |
|--------------------------------|----------------------------------------------------|
| Approvals                      | CE, UL (yellow lid models not included)            |
| Compliance with standards      | IEC-60529, UL508A, UL50, UL50E, CSA C22.2 No.14-13 |
| Operating temperatures         | -35° ÷ +80° C                                      |
| Protection degree              | IP66 - IP69K - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact      | IK08 (IEC-EN62262)                                 |
| Enclosure material             | PC Polycarbonate - glass fibre reinforced          |
| Gasket material                | Polyurethane foam                                  |
| Screw material                 | PA Black Polyamide - fiber glass reinforced        |
| Tightening torque              | 0.8 ÷ 1.2Nm (7.1 ÷ 10.6 Lb-in)                     |
| Overvoltage category           | Class II (IEC-EN61140)                             |
| Heavy metal-free               | yes                                                |
| PVC-free                       | yes                                                |
| Silicon-free                   | yes                                                |
| Halogen-free                   | yes                                                |
| Combustion behaviour           | 5VA (UL50 - UL746C)                                |
| Combustion behaviour           | V-2 (UL94)                                         |
| Combustion behaviour           | 960°(EN-IEC 60695-2-11)                            |
| Fitted for outdoor application | yes                                                |
| Warranty period                | 18 months                                          |

## Data sheet

080C0918-8P5L

Scatola pulsantiera in policarbonato 94x180x81, 5 fori Ø 22

## Technical drawings

