





L10F (fisso - fixed)

Code	Frame	Nominal/lm	Real/lm	LED/W	System/W	CCT	Beam
L10F/WCM/3K22/_		2100	1925	22	24	3000K	25°
L10F/WCM/4K22/_	W	2200	2017	22	24	4000K	25°
L10F/WCF/3K22/_		2100	1780	22	24	3000K	40°
L10F/WCF/4K22/_		2200	1865	22	24	4000K	40°
L10F/BCM/3K22/_		2100	1925	22	24	3000K	25°
L10F/BCM/4K22/_	B	2200	2017	22	24	4000K	25°
L10F/BCF/3K22/_		2100	1780	22	24	3000K	40°
L10F/BCF/4K22/_		2200	1865	22	24	4000K	40°



Incastro a LED per installazione a soffitto. Versione fissa.

LED OSRAM CRI>90

Lifetime 50.000h (L70B10).

Corpo in alluminio. Cornice bianco o nera.

Riflettori in policarbonato in 4 finiture diverse:
 B= nero
 M= argento opaco
 W= bianco
 G= oro

Alimentatore 220-240V - 50/60Hz incluso.

Recessed LED fitting for false ceiling installation. Fixed version.

OSRAM LED CRI>90

Lifetime 50.000h (L70B10).

Body in aluminium. White or black frame.

Polycarbonate reflector in 4 different finishing:
 B= black
 M= silver mat
 W= white
 G= gold

220-240V - 50/60Hz power supply included.

Appareil à encastrer LED pour installation dans faux-plafond. Version fixe.

LED OSRAM IRC>90

Durée de vie 50.000h (L70B10).

Corps en aluminium. Cadre blanc ou noir.

Réflecteur en polycarbonate en 3 finitions différentes :
 B= noir
 M= argent mat
 W= blanc
 G= or

Alimentation 220-240V - 50/60Hz incluse.

LED-Einbau für Deckeninstallation in 3 Massen.





LED OSRAM CRI>90

Lebensdauer 50.000h (L70B10).

Körper Aluminium. Weißer oder schwarzer Rahmen

Polycarbonat Reflektor in 4 verschiedenen Ausführungen:
 B= Schwarz
 M= Silber matt
 W= Weiss
 G= Gold

Netzgerät 220-240V - 50/60Hz enthalten.




Versioni prodotto disponibili su richiesta - Product versions available upon request - Versions du produit disponibles sur demande - Produktversion auf Anfrage erhältlich

Code	Description
L10F/___/___/___/1	ON-OFF Made in Italy
L10F/___/___/___/2	PUSH/DIM 1-10V Made in Italy
L10F/___/___/___/3	DALI Made in Italy
L10F/___/___/___/6	ON-OFF
L10F/___/___/___/9	Wi-Fi ZIGBEE Made in Italy (Zigbee gateway, not included)
L10F/___/___/___/10	Bluetooth BLL Made in Italy (by APP BLL PLUS: IOS/Android)
L10F/___/___/___/11	Bluetooth CASAMBI Made in Italy (by APP CASAMBI: IOS/Android)

Gestione della luce / Light management, see cat.42



Kit emergenza disponibile su richiesta - Emergency kit available upon request - Kit éclairage secours disponible sur demande - Notfall Kit auf Anfrage erhältlich.

Code	Descrizione	Description	Description	Beschreibung
KIT EM/LED/1H	Kit emergenza per LED 1 ora - Batt.7.2V - 1.5Ah	Emergency kit for LED 1 hour - Batt.7.2V - 1.5Ah	Kit éclairage secours pour LED 1 heure - Batt.7.2V - 1.5Ah	Notfall Kit für LED 1 Stunde - Batt.7.2V - 1.5Ah
KIT EM/LED/3H	Kit emergenza per LED 3 ore - Batt.7.2V - 4Ah	Emergency kit for LED 3 hours - Batt.7.2V - 4Ah	Kit éclairage secours pour LED 3 heures - Batt.7.2V - 4Ah	Notfall Kit für LED 3 Stunden - Batt.7.2V - 4Ah



L10A (orientabile - adjustable)

Code	Frame	Nominal/lm	Real/lm	LED/W	System/W	CCT	Beam
L10A/WCM/3K22/_		2100	1925	22	24	3000K	25°
L10A/WCM/4K22/_	W	2200	2017	22	24	4000K	25°
L10A/WCF/3K22/_		2100	1780	22	24	3000K	40°
L10A/WCF/4K22/_		2200	1865	22	24	4000K	40°
L10A/BCM/3K22/_		2100	1925	22	24	3000K	25°
L10A/BCM/4K22/_	B	2200	2017	22	24	4000K	25°
L10A/BCF/3K22/_		2100	1780	22	24	3000K	40°
L10A/BCF/4K22/_		2200	1865	22	24	4000K	40°



Incasso a LED per installazione a soffitto. Versione orientabile.

Recessed LED fitting for false ceiling installation. Adjustable version.

Appareil à encastrer LED pour installation dans faux-plafond. Version réglable.

LED-Einbau für Deckeninstallation in 3 Massen.

LED OSRAM CRI>90

OSRAM LED CRI>90

LED OSRAM IRC>90

LED OSRAM CRI>90

Lifetime 50.000h (L70B10).

Lifetime 50.000h (L70B10).

Durée de vie 50.000h (L70B10).

Lebensdauer 50.000h (L70B10).

Corpo in alluminio. Cornice bianco o nera.

Body in aluminium. White or black frame.

Corps en aluminium. Cadre blanc ou noir.

Körper Aluminium. Weißer oder schwarzer Rahmen

Riflettori in policarbonato in 4 finiture diverse:
B= nero
M= argento opaco
W= bianco
G= oro

Polycarbonate reflector in 4 different finishing:
B= black
M= silver mat
W= white
G= gold

Réflecteur en polycarbonate en 3 finitions différentes :
B= noir
M= argent mat
W= blanc
G= or





Polycarbonat Reflektor in 4 verschiedenen Ausführungen:
B= Schwarz
M= Silber matt
W= Weiss
G= Gold

Alimentatore 220-240V - 50/60Hz incluso.

220-240V - 50/60Hz power supply included.

Alimentation 220-240V - 50/60Hz incluse.

Netzgerät 220-240V - 50/60Hz enthalten.



Versioni prodotto disponibili su richiesta - Product versions available upon request - Versions du produit disponibles sur demande - Produktversion auf Anfrage erhältlich

Code	Description
L10A/___/___/_1	ON-OFF Made in Italy
L10A/___/___/_2	PUSH/DIM1-10V Made in Italy
L10A/___/___/_3	DALI Made in Italy
L10A/___/___/_6	ON-OFF
L10A/___/___/_9	Wi-Fi ZIGBEE Made in Italy (Zigbee gateway, not included)
L10A/___/___/_10	Bluetooth BLL Made in Italy (by APP BLL PLUS: IOS/Android)
L10A/___/___/_11	Bluetooth CASAMBI Made in Italy (by APP CASAMBI: IOS/Android)

Gestione della luce / Light management, see cat.42

Kit emergenza disponibile su richiesta - Emergency kit available upon request - Kit éclairage secours disponible sur demande - Notfall Kit auf Anfrage erhältlich.


Code	Descrizione	Description	Description	Beschreibung
KIT EM/LED/1H	Kit emergenza per LED 1 ora - Batt.7.2V - 1.5Ah	Emergency kit for LED 1 hour - Batt.7.2V - 1.5Ah	Kit éclairage secours pour LED 1 heure - Batt.7.2V - 1.5Ah	Notfall Kit für LED 1 Stunde - Batt.7.2V - 1.5Ah
KIT EM/LED/3H	Kit emergenza per LED 3 ore - Batt.7.2V - 4Ah	Emergency kit for LED 3 hours - Batt.7.2V - 4Ah	Kit éclairage secours pour LED 3 heures - Batt.7.2V - 4Ah	Notfall Kit für LED 3 Stunden - Batt.7.2V - 4Ah



L10F/___W (wallwasher)

Code	Frame	Nominal/lm	Real/lm	LED/W	System/W	CCT	Beam
L10F/WCW/3K22/M	W	2100	999	22	24	3000K	--
L10F/WCW/4K22/M	W	2200	1047	22	24	4000K	--
L10F/BCW/3K22/M	B	2100	999	22	24	3000K	--
L10F/BCW/4K22/M	B	2200	1047	22	24	4000K	--

3 ANNI DI GARANZIA
3 YEARS OF GUARANTEE



Incasso a LED per installazione a soffitto. Versione wallwasher.

Recessed LED fitting for false ceiling installation. Wallwasher version.

Appareil à encastrer LED pour installation dans faux-plafond. Version wallwasher.

LED-Einbau für Deckeninstallation in 3 Massen.

LED OSRAM CRI>90

OSRAM LED CRI>90

LED OSRAM IRC>90

LED OSRAM CRI>90

Lifetime 50.000h (L70B10).

Lifetime 50.000h (L70B10).

Durée de vie 50.000h (L70B10).

Lebensdauer 50.000h (L70B10).

Corpo in alluminio. Cornice bianco o nera.

Body in aluminium. White or black frame.

Corps en aluminium. Cadre blanc ou noir.

Körper Aluminium. Weißer oder schwarzer Rahmen

Riflettore in policarbonato: M= argento opaco

Polycarbonate reflector: M= silver mat

Réflecteur en polycarbonate: M= argent mat


Polycarbonat Reflektor: M= Silber matt

Alimentatore 220-240V - 50/60Hz incluso.

220-240V - 50/60Hz power supply included.

Alimentation 220-240V - 50/60Hz incluse.

Netzgerät 220-240V - 50/60Hz enthalten.



Versioni prodotto disponibili su richiesta - Product versions available upon request - Versions du produit disponibles sur demande - Produktversion auf Anfrage erhältlich

Code	Description
L10F/___W/___/M1	ON-OFF Made in Italy
L10F/___W/___/M2	PUSH/DIM 1-10V Made in Italy
L10F/___W/___/M3	DALI Made in Italy
L10F/___W/___/M6	ON-OFF
L10F/___W/___/M9	Wi-Fi ZIGBEE Made in Italy (Zigbee gateway, not included)
L10F/___W/___/M10	Bluetooth BLL Made in Italy (by APP BLL PLUS: IOS/Android)
L10F/___W/___/M11	Bluetooth CASAMBI Made in Italy (by APP CASAMBI: IOS/Android)

Gestione della luce / Light management, see cat.42

Kit emergenza disponibile su richiesta - Emergency kit available upon request - Kit éclairage secours disponible sur demande - Notfall Kit auf Anfrage erhältlich

Code	Descrizione	Description	Description	Beschreibung
KIT EM/LED/1H	Kit emergenza per LED 1 ora - Batt.7.2V - 1.5Ah	Emergency kit for LED 1 hour - Batt.7.2V - 1.5Ah	Kit éclairage secours pour LED 1 heure - Batt.7.2V - 1.5Ah	Notfall Kit für LED 1 Stunde - Batt.7.2V - 1.5Ah
KIT EM/LED/3H	Kit emergenza per LED 3 ore - Batt.7.2V - 4Ah	Emergency kit for LED 3 hours - Batt.7.2V - 4Ah	Kit éclairage secours pour LED 3 heures - Batt.7.2V - 4Ah	Notfall Kit für LED 3 Stunden - Batt.7.2V - 4Ah