




5 ANNI DI GARANZIA
YEARS OF GUARANTEE

MMRA/C

Code	Nominal/lm	Real/lm	LED/W	System/W	CCT	Beam
MMRA/CM/2K04/_	480	333	4	6	2700K	20°
MMRA/CM/3K04/_	500	347	4	6	3000K	20°
MMRA/CM/4K04/_	550	382	4	6	4000K	20°
MMRA/CF/2K04/_	480	283	4	6	2700K	40°
MMRA/CF/3K04/_	500	295	4	6	3000K	40°
MMRA/CF/4K04/_	550	324	4	6	4000K	40°



Ø55

CRI >90	45mm	M	F	DRIVER INCLUDED	UGR <16	IP20	CE	F		A++	A+	A
---------	------	---	---	-----------------	---------	------	----	---	--	-----	----	---

Incasso orientabile tondo a LED per installazione a soffitto.

Round adjustable recessed LED fitting for false ceiling installation.

Appareil à encastrer LED orientable rond pour installation dans faux-plafond

Runder, LED-Einbau für Deckeninstallation

LED CREE CRI>90

CREE LED CRI>90

LED CREE IRC>90

LED CREE CRI>90

Life time 50.000h (L70B10).

Life time 50.000h (L70B10).

Durée de vie 50.000h (L70B10).

Lebensdauer 50.000h (L70B10).

Corpo in alluminio pressofuso.

Body in die-cast aluminium.

Corps en fonderie d'aluminium.

Aluminium-Druckguss Körper.

Cornice in alluminio verniciato bianco.

Frame in white painted aluminium.

Cadre en aluminium peint blanc.

Weiss lackierter Aluminium Rahmen.

Doppio sistema ottico con lente e riflettore che migliora il comfort visivo.

Double optical system with lens and reflector to improve the visual comfort.

Double système optique avec lentille et réflecteur pour un meilleur confort visuel.

Dual-optisches System mit einer Linse und Reflektor die den Sehkomfort verbessern.

Disponibili accessori intercambiabili:
- riflettore in policarbonato in tre finiture diverse;
- griglia anti abbagliamento.

Interchangeable accessories available upon request:
- polycarbonate reflector in 3 different finishing;
- anti-glare grid.

Disponibles accessoires interchangeables:
- réflecteur en polycarbonate en 3 finitions différentes;
- grille anti éblouissement.





Austauschbare Zubehör erhältlich:
- Polycarbonat Reflektor in 3 verschiedenen Ausführungen;
- Entblendungs Gitter.

Alimentatore 220-240V - 50/60Hz incluso. (ON-OFF, PUSH, DIM 1-10V, DALI)

220-240V - 50/60Hz power supply included. (ON-OFF, PUSH, DIM 1-10V, DALI)

Alimentation 220-240V - 50/60Hz incluse. (ON-OFF, PUSH, DIM 1-10V, DALI)

Netzgerät 220-240V - 50 / 60Hz enthalten. (ON-OFF, PUSH, DIM 1-10V, DALI)



Completare il codice prodotto identificando il driver - Choose the driver version you need to complete the product's code

Code	Descrizione	Description	Description	Beschreibung
MMRA/C/_/_/_/_/1	Con driver ON-OFF Made in Italy	With Made in Italy ON-OFF driver	Avec alimentation ON-OFF Made in Italy	Mit Driver ON-OFF Made in Italy
MMRA/C/_/_/_/_/2	Con driver DIM 1-10V Made in Italy	With Made in Italy DIM 1-10V driver	Avec alimentation DIM 1-10V Made in Italy	Mit Driver DIM 1-10V Made in Italy
MMRA/C/_/_/_/_/2P	Con driver PUSH Made in Italy	With Made in Italy PUSH driver	Avec alimentation PUSH Made in Italy	Mit Driver PUSH Made in Italy
MMRA/C/_/_/_/_/3	Con driver DALI Made in Italy	With Made in Italy DALI driver	Avec alimentation DALI Made in Italy	Mit Driver DALI Made in Italy
MMRA/C/_/_/_/_/6	Con driver ON-OFF	With ON-OFF driver	Avec alimentation ON-OFF	Mit Driver ON-OFF
MMRA/C/_/_/_/_/7	Con driver DIM 1-10V	With DIM 1-10V driver	Avec alimentation DIM 1-10V	Mit Driver DIM 1-10V

Accessori disponibili su richiesta - Accessories available upon request

Code	Descrizione	Description
5861	Interfaccia Bluetooth regolazione tramite APP o pulsante NA. Solo per versione /2	Bluetooth interface, control via App or NO button. Only for version /2
5864	Interfaccia Wi-Fi regolazione tramite gateway Zigbee (non fornito). Solo per versione /2	Wi-Fi interface through Zigbee gateway (not included). Only for version /2

Kit emergenza disponibile su richiesta - Emergency kit available upon request - Kit éclairage secouru disponible sur demande - Notfall Kit auf Anfrage erhältlich.

Code	Descrizione	Description	Description	Beschreibung
KIT EM/LED/1H	Kit emergenza per LED 1 ora - Batt.7.2V - 1.5Ah	Emergency kit for LED 1 hour - Batt.7.2V - 1.5Ah	Kit éclairage secouru pour LED 1 heure - Batt.7.2V - 1.5Ah	Notfall Kit für LED 1 Stunde - Batt.7.2V - 1.5Ah
KIT EM/LED/3H	Kit emergenza per LED 3 ore - Batt.7.2V - 4Ah	Emergency kit for LED 3 hours - Batt.7.2V - 4Ah	Kit éclairage secouru pour LED 3 heures - Batt.7.2V - 4Ah	Notfall Kit für LED 3 Stunden - Batt.7.2V - 4Ah