





Caratteristiche

Uso: Interno
Ottica: MICROPRISMATIZZATO
L: 1680mm
A: 48mm
H: 6mm
Made in: ITALY
Garanzia: 5 anni
Peso: 0.4kg

Dati tecnici

IP: 40
UGR: <19

Luminanza media

Limite di luminanza in ambienti con videotermini: Inferiore alle 3000 cd/mq per angoli > 65° (secondo EN 12464-1:2011).



ACCESSORI DI COMPLETAMENTO

	HERO: MOD.CIECO 250 CAP	108676.21
	HERO: MOD.CIECO ANG.SX 150 CAP	108677.21
	HERO: MOD.CIECO ANG.DX 150 CAP	108678.21
	HERO: MOD.CIECO 1120 CAP	108679.21
	HERO: MOD.CIECO 1400 CAP	108680.21
	HERO: MOD.CIECO 1680 CAP	108681.21
	HERO: COPPIA TESTATE CAP	108684.21

ACCESSORI DI MONTAGGIO

	HERO: SOSPL.3000 1PZ TESTA W.G.ALTO	1086A1.99
	HERO: SOSPL.3000 1PZ UNIONE W.G.ALTO	1086A2.99
	ALL-TRACK: COPPIA ADATT. 3P+DALI BIA	106723.01
	ALL-TRACK: COPPIA ADATT. 3P+DALI NER	106723.02

	HERO: SOSP.L3000 1PZ. TESTA/CODA	108685.99
	HERO: SOSP.L3000 1PZ. UNIONE	108686.99
	HERO: STAFFA PARETE "L" CAP	108687.21
	HERO: KIT INCASSO LED (1X)	108688.99
	HERO: SPESS. CARTONG. 10MM 2PZ.	108689.99
	KIT ALIMENTAZIONE L1200 5P CAP	108921.21
	KIT ALIMENTAZIONE L3000 5P CAP	108922.21