



Caratteristiche

Uso: Interno

Tipo installazione: PARETE, INCASSO IN CARTONGESSO, SOSPENSIONE, PLAFONE, BINARIO

Emissione: DIRETTA

Ottica: OPALE

Colore: BIANCO

Dimmerazione: PUSH, DALI

Emergenza: Autonomia 1h/Ricarica 12h

L: 1680mm

A: 53mm

H: 69mm

Made in: ITALY

Garanzia: 5 anni eccetto batteria

Peso: 6.2kg

Dati tecnici

Potenza reale apparecchio: 55W

Flusso luminoso apparecchio: 3740lm

Flusso luminoso in emergenza: 10%

IP: 40

Classe di isolamento: I

Tensione di alimentazione: 220-240V 50/60Hz

SELV: Sì

Sorgente

Sorgente luminosa: LED

Potenza sorgente: 49W

Temperatura colore: 3000K

CRI: >90

Tolleranza colore: 3 Step MacAdam

LED lifespan: 50000h L80 B20

Conformità

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012, CEI EN 60598-2-22:2023

Norme

Rischio fotobiologico: GRUPPO RISCHIO 0 Apparecchio certificato in GRUPPO ESENTE DA RISCHI, in conformità alla normativa CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: Conforme al Decreto Ministeriale 23 giugno 2022 n.256.

[Visualizza maggiori info sul prodotto](#)

HERO

1086B0.01 + 108903.99

HERO: EM 49W 3K 1680 DALI BIA + HERO: DIFF. OPALE PER 1680



novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Caratteristiche

Uso: Interno
Ottica: OPALE
L: 1680mm
A: 48mm
H: 6mm
Made in: ITALY
Garanzia: 5 anni
Peso: 0.4kg

Dati tecnici

IP: 40



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · P.IVA 00536541204 · novalux.com
Società soggetta ad attività di direzione e coordinamento da parte di SLV GmbH

La presente scheda tecnica è di proprietà di Novalux S.r.l., tutti i diritti riservati. Novalux S.r.l. si riserva il diritto di apportare modifiche senza preavviso alcuno.
Ultimo aggiornamento: 29/4/2024, 14:06:06

Technical drawing of the HERO: MOD.CIECO 250 BIA profile. It shows a cross-section with dimensions: H 135, L 165, W 93, and a length dimension L. The profile has a channel shape with a flange on one side.	HERO: MOD.CIECO 250 BIA 108676.01
Technical drawing of the HERO: MOD.CIECO ANG.SX 150 BIA profile. It shows a cross-section with dimensions: H 135, L 150x150, W 93, and a length dimension L. The profile is an L-shaped corner piece.	HERO: MOD.CIECO ANG.SX 150 BIA 108677.01
Technical drawing of the HERO: MOD.CIECO ANG.DX 150 BIA profile. It shows a cross-section with dimensions: H 135, L 150x150, W 93, and a length dimension L. The profile is an L-shaped corner piece, similar to the previous one but with a different orientation.	HERO: MOD.CIECO ANG.DX 150 BIA 108678.01
Technical drawing of the HERO: MOD.CIECO 1120 BIA profile. It shows a cross-section with dimensions: H 135, L 165, W 93, and a length dimension L. The profile is a channel shape with a flange on one side.	HERO: MOD.CIECO 1120 BIA 108679.01
Technical drawing of the HERO: MOD.CIECO 1400 BIA profile. It shows a cross-section with dimensions: H 135, L 165, W 93, and a length dimension L. The profile is a channel shape with a flange on one side.	HERO: MOD.CIECO 1400 BIA 108680.01
Technical drawing of the HERO: MOD.CIECO 1680 BIA profile. It shows a cross-section with dimensions: H 135, L 165, W 93, and a length dimension L. The profile is a channel shape with a flange on one side.	HERO: MOD.CIECO 1680 BIA 108681.01
Technical drawing of the HERO: COPPIA TESTATE BIA profile. It shows a cross-section with dimensions: H 81, L 2, W 81, and a length dimension L. The profile is a small rectangular piece.	HERO: COPPIA TESTATE BIA 108684.01

	HERO: SOSP.L3000 1PZ TESTA W.G.ALTO	1086A1.99
	HERO: SOSP.L3000 1PZ UNIONE W.G.ALTO	1086A2.99
	HERO: SOSP.L3000 1PZ. TESTA/CODA	108685.99
	HERO: SOSP.L3000 1PZ. UNIONE	108686.99



HERO: STAFFA PARETE "L" BIA

108687.01



HERO: KIT INCASSO LED (1X)

108688.99



HERO: SPESS. CARTONG. 10MM 2PZ.

108689.99



KIT ALIMENTAZIONE L1200 5P BIA

108921.01



KIT ALIMENTAZIONE L3000 5P BIA

108922.01