

Caratteristiche

Uso: Interno
 Tipo installazione: INCASSO IN CARTONGESSO, PLAFONE
 Emissione: DIRETTA
 Ottica: MICROPRISMATIZZATO
 Colore: BIANCO
 Dimmerazione: NO
 Emergenza: CON ACCESSORIO
 L: 595mm
 A: 595mm
 H: 35mm
 Garanzia: 3 anni
 Peso: 2.47kg

Dati tecnici

Potenza reale apparecchio: 36W
Flusso luminoso apparecchio: 3807lm
Flusso luminoso in emergenza: 1h: 12% / 3h: 5
IP: 40
Classe di isolamento: II
N° Driver per prodotto: 1
Tensione di alimentazione: 900mA driver incluso
UGR: <19 4H-8H S=0,25
IK: 5
SELV: Sì

Sorgente

Sorgente luminosa: LED
Potenza sorgente: 32W
Flusso luminoso sorgente: 5112lm
Temperatura colore: 3000K
CRI: >80
LED lifespan: 50000h L80 B20

Conformità

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Norme

Rischio fotobiologico: GRUPPO RISCHIO 0Apparecchio certificato in GRUPPO ESENTE DA RISCHI, in conformità alla normativa CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: Conforme al Decreto Ministeriale 23 giugno 2022 n.256.

Technical drawing of a square frame structure. The drawing shows a square base with dimensions 600 and 600. A vertical dimension of 3000 is indicated on the right side. The drawing includes lines representing the frame's structure and a small detail view of a corner joint.


113637.01



108921.01



108922.01



102028.99




108919.01



113639.99




113620.99




113610.01



108920.01



1020A5.99



THE PANEL 2: EMER.INC.1H 10/54VDC

1020A4.99