

SERIE CH

CH series | Série CH



FUSIBILI 14x51 gG 14x51 gG fuses | Fusibles 14x51 gG

Caratteristica Rapidi	Characteristic Fast	Caractéristique Rapides
Tensione 400 V/690 V	Voltage 400 V/690 V	Tension 400 V/690 V
Corpo Ceramica	Body Ceramic	Corps Céramique
Capacità di rottura 80.000 A	Breaking capacity 80.000 A	Pouvoir de coupure 80.000 A
Norme riferimento IEC 60 269/2-1 VDE 0636 UNE 21103 CEI 32/1-4 NFC 63210	Standards IEC 60 269/2-1 VDE 0636 UNE 21103 CEI 32/1-4 NFC 63210	Normes IEC 60 269/2-1 VDE 0636 UNE 21103 CEI 32/1-4 NFC 63210
Marchio di fabbrica OMEGA Ω	Trade mark OMEGA Ω	Marque de fabrique OMEGA Ω



pag. 19



Corrente nom. Rated current Courant nominal	Codice Code Code	Codice Code Code	Tensione Voltage Tension
2 A	gl151220	gls151220	690 V
4 A	gl151240	gls151240	690 V
6 A	gl151260	gls151260	690 V
10 A	gl151310	gls151310	690 V
16 A	gl151316	gls151316	690 V
20 A	gl151320	gls151320	690 V
25 A	gl151325	gls151325	690 V
• 32 A	gl151332	gls151332	500 V
• 40 A	gl151440	gls151440	500 V
• 50 A	gl151450	gls151450	400 V

a richiesta sono fornibili i fusibili con striker
fuses with striker upon request
sur demande, nous pouvons fournir ces fusibles
avec un percuteur

gls: con segnalino di fusione
with blowing indicator
avec indicateur de fusion

10/50 pz
10/50 pcs
10/50 pces

pronta
in stock
en stock

• capacità di rottura 120 KA
breaking capacity 120 KA
pouvoir de coupure 120 KA



FUSIBILI 22x58 gG 22x58 gG fuses | Fusibles 22x58 gG

Caratteristica Rapidi	Characteristic Fast	Caractéristique Rapides
Tensione 400 V/690 V	Voltage 400 V/690 V	Tension 400 V/690 V
Corpo Ceramica	Body Ceramic	Corps Céramique
Capacità di rottura 80.000 A	Breaking capacity 80.000 A	Pouvoir de coupure 80.000 A
Norme riferimento IEC 60 269/2-1 VDE 0636 UNE 21103 CEI 32/1-4 NFC 63210	Standards IEC 60 269/2-1 VDE 0636 UNE 21103 CEI 32/1-4 NFC 63210	Normes IEC 60 269/2-1 VDE 0636 UNE 21103 CEI 32/1-4 NFC 63210
Marchio di fabbrica OMEGA Ω	Trade mark OMEGA Ω	Marque de fabrique OMEGA Ω



pag. 19



Corrente nom. Rated current Courant nominal	Codice Code Code	Codice Code Code	Tensione Voltage Tension
16 A	gl258316	gls258316	690 V
20 A	gl258320	gls258320	690 V
25 A	gl258325	gls258325	690 V
32 A	gl258332	gls258332	690 V
40 A	gl258440	gls258440	690 V
50 A	gl258450	gls258450	690 V
63 A	gl258463	gls258463	690 V
80 A	gl258480	gls258480	500 V
• 100 A	gl258100	gls258100	500 V
• 125 A	gl258125	gls258125	400 V

a richiesta sono fornibili i fusibili con striker
fuses with striker upon request
sur demande, nous pouvons fournir ces fusibles
avec un percuteur

gls: con segnalino di fusione
with blowing indicator
avec indicateur de fusion

10/50 pz
10/50 pcs
10/50 pces

pronta
in stock
en stock

• capacità di rottura 120 KA
breaking capacity 120 KA
pouvoir de coupure 120 KA