

Tak-Tape™ Hook & Loop Cable Rolls

specifications

Tak-Tape™ Hook & Loop Rolls shall be strong, low profile, flexible materials that shall be safe to use on high performance cabling. This shall aid in protection against over tensioning. This product shall be adjustable, reusable and a cost-effective method for properly bundling cable. The Tak-Tape™ Hook & Loop Rolls shall be available in black and shall come in a variety of packages as showcased below:



TTR-20R0



TTR-35R3-0



TTR-35RX0



TTR-75R0

technical information

Dimensions: Length: Various
Width: 0.75" (19.1mm)

Material: Hooks: Nylon
Loops: Nylon

Minimum loop tensile strength: 40 Lbs. (178 N)

key features and benefits

Various sizes available Low-profile hook and loop is available in different sizes that can easily be used to bundle cable

Enhanced protection Provides enhanced protections for cables to ensure better bundling

Part Number	Unit of Measurement	Packaging	Colour
Low Profile Hook and Loop Roll			
TTR-20R0	20'L (6.1m), 0.75" W (19.1mm)	—	Black
TTR-35R3-0	35' L (10.7m), 0.75" W (19.1mm)	3-Roll	
TTR-35RX0		10-Roll	
TTR-75R0	75' L (22.8m), 0.75" W (19.1mm)	—	

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT US/CANADA
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA
Guadalajara, Mexico
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty