

- Increased operating distance
- 8 mm quasi flush



Technical drawing of the LED light fixture showing dimensions and specifications:


- Top mounting hole: M12 x 1
- Top mounting hole diameter: 4
- Top mounting hole offset: 17
- LED chip diameter: $\varnothing 10.5$
- LED chip quantity: LED (4x)
- LED chip offset: 8
- LED chip diameter: M12 x 1
- LED chip offset: 41
- LED chip offset: 49
- LED chip offset: 60

General specifications		
Switching function		Normally open (NO)
Output type		PNP
Rated operating distance	s _n	8 mm
Installation		quasi flush
Output polarity		DC
Assured operating distance	s _a	0 ... 6.48 mm
Reduction factor r _{AI}		0.3
Reduction factor r _{CU}		0.25
Reduction factor r ₃₀₄		0.7
Reduction factor r _{St37}		1
Output type		3-wire
Nominal ratings		
Installation conditions		
A		2 mm
B		14 mm
C		24 mm


Technical Data

F		46 mm
Operating voltage	U_B	10 ... 30 V
Switching frequency	f	0 ... 400 Hz
Hysteresis	H	≤ 10 %
Reverse polarity protection		reverse polarity protected
Short-circuit protection		yes
Voltage drop	U_d	≤ 2 V
Operating current	I_L	0 ... 200 mA
Off-state current	I_r	0 ... 0.1 mA typ. 0.1 µA at 25 °C
No-load supply current	I_0	≤ 10 mA
Switching state indicator		LED, yellow
Functional safety related parameters		
MTTF _d		602 a
Mission Time (T _M)		20 a
Diagnostic Coverage (DC)		0 %
Compliance with standards and directives		
Standard conformity		
Standards		EN IEC 60947-5-2
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
CCC approval		CCC approval / marking not required for products rated ≤36 V
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		Connector plug
Housing material		chromium plated brass
Sensing face		PBT
Degree of protection		IP67
Protection class		II
Connector		
Threading		M12 x 1
Number of pins		4
Mass		34 g
Dimensions		
Length		60 mm
Diameter		12 mm
Tightening torque		≤ 10 Nm (6 Nm for the first 10 mm thread length)

Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
2	WH	(white)
3	BU	(blue)
4	BK	(black)

Installation Conditions

