



## AS-Interface Handheld with accessory VBP-HH1-V3.0-KIT

- Addressing and programming AS-Interface nodes
- Displaying the assigned node addresses and the status of the inputs
- Setting outputs at the AS-Interface node
- Also supports profiles S-7.7.A.7 (Spec 3.0), S-0.B and S-7.B (AS Interface Safety at Work)
- The node connection is short-circuit and overload proof
- Battery charger for EU, USA, UK, and AU included in the scope of delivery

### AS-Interface Handheld with accessory



### Function


The AS-Interface handheld VBP-HH1-V3.0 is an addressing device according to the AS-Interface specification 3.0. This addressing device can be used to program AS-Interface nodes and to test part of their functions. In addition, new functions have been incorporated:

- Permanent data exchange with AS-Interface nodes
- Support of the data exchange with 4E4A nodes in ext. addressing mode
- Indication of the safety code for AS-Interface Safety at Work nodes

The AS-Interface connection adapter on the top of the addressing device is used for connecting AS-Interface nodes such as sensors, actuators and modules to the addressing device. The following devices and designs can be connected to the addressing device by directly plugging it onto the AS-Interface connection adapter:

Devices with M12 connector, VariKont M-system, VariKont system, FP design, AS-Interface modules of the types G1 and G4. For device designs with integrated addressing socket, use the optional adapter cable.

### Dimensions



### Technical Data

#### General specifications

AS-Interface specification

V3.0

#### Indicators/operating means

Release date: 2025-02-25 Date of issue: 2025-02-25 Filename: 229188\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**

## Technical Data


|                                  |       |                                                                                                                                                                                                                                                                                                                  |
|----------------------------------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display                          |       | LC display                                                                                                                                                                                                                                                                                                       |
| Keyboard                         |       | membrane keys, 5 keys                                                                                                                                                                                                                                                                                            |
| <b>Electrical specifications</b> |       |                                                                                                                                                                                                                                                                                                                  |
| Operating duration               |       | 8 h or $\geq 250$ read/write procedures for fully charged battery                                                                                                                                                                                                                                                |
| Operating voltage                | $U_B$ | Plug-in charging unit 90 ... 264 V AC                                                                                                                                                                                                                                                                            |
| Power supply                     |       | battery mode, please use only battery charger included with delivery to charge (charging time about 14 h)                                                                                                                                                                                                        |
| <b>Interface</b>                 |       |                                                                                                                                                                                                                                                                                                                  |
| Interface type                   |       | AS-Interface, short-circuit proof and overload-proof, or optical                                                                                                                                                                                                                                                 |
| Open loop voltage                |       | 28 V                                                                                                                                                                                                                                                                                                             |
| Load current                     |       | 100 mA at 25 V                                                                                                                                                                                                                                                                                                   |
| <b>Directive conformity</b>      |       |                                                                                                                                                                                                                                                                                                                  |
| Electromagnetic compatibility    |       |                                                                                                                                                                                                                                                                                                                  |
| Directive 2014/30/EU             |       | Handheld: EN 61326-1:2013<br>Plug-in charging unit EN 61000-3-2:2014 , EN 61000-3-3:2013 , EN 61000-4-2:2009 , EN 61000-4-3:2006+A1:2008+A2:2010, EN 61000-4-4:2012, EN 61000-4-5:2014+A1:2017, EN 61000-4-6:2014+AC:2015, EN 61000-4-8:2010, EN 61000-4-11:2004+A1:2017 , EN 55032:2015+AC:2016 , EN 55035:2017 |
| Low voltage                      |       |                                                                                                                                                                                                                                                                                                                  |
| Directive 2014/35/EU             |       | Plug-in charging unit EN 62368-1:2014+A11:2017                                                                                                                                                                                                                                                                   |
| <b>Standard conformity</b>       |       |                                                                                                                                                                                                                                                                                                                  |
| Degree of protection             |       | EN 60529:2000                                                                                                                                                                                                                                                                                                    |
| Electrical safety                |       | Plug-in charging unit EN 62368-1:2014+A11:2017                                                                                                                                                                                                                                                                   |
| Emitted interference             |       | Handheld: EN 61326-1:2013<br>Plug-in charging unit EN 55032:2015+AC:2016 , EN 55035:2017                                                                                                                                                                                                                         |
| Noise immunity                   |       | Handheld: EN 61326-1:2013<br>Plug-in charging unit EN 61000-3-2:2014 , EN 61000-3-3:2013                                                                                                                                                                                                                         |
| <b>Ambient conditions</b>        |       |                                                                                                                                                                                                                                                                                                                  |
| Ambient temperature              |       | 0 ... 40 °C (32 ... 104 °F)                                                                                                                                                                                                                                                                                      |
| Storage temperature              |       | -20 ... 40 °C (-4 ... 104 °F)                                                                                                                                                                                                                                                                                    |
| <b>Mechanical specifications</b> |       |                                                                                                                                                                                                                                                                                                                  |
| Degree of protection             |       | IP20                                                                                                                                                                                                                                                                                                             |
| Connection                       |       | Plug-in charger 90 ... 264 V <sub>AC</sub> with interchangeable plug for EU, USA, UK and AU included with delivery                                                                                                                                                                                               |
| <b>Material</b>                  |       |                                                                                                                                                                                                                                                                                                                  |
| Housing                          |       | plastic                                                                                                                                                                                                                                                                                                          |
| Mass                             |       | approx. 1000 g                                                                                                                                                                                                                                                                                                   |
| <b>Dimensions</b>                |       |                                                                                                                                                                                                                                                                                                                  |
| Height                           |       | 34 mm                                                                                                                                                                                                                                                                                                            |
| Width                            |       | 80 mm                                                                                                                                                                                                                                                                                                            |
| Length                           |       | 214 mm                                                                                                                                                                                                                                                                                                           |

## Connection



- 1 AS-Interface +
- 2 Digital input for optical addressing adapters
- 3 AS-Interface -
- 4 Digital output for optical addressing adapters
- 5 Voltage supply for optical addressing adapters

Assembly



Scope of Delivery

The set VBP-HH1-V3.0-KIT consists of the addressing device VBP-HH1-V3.0, a universal plug-in charger and the connecting cable module / handheld VAZ-PK-1,5M-V1-G in a matching case.