




Inductive sensor NBB10-30GM50-Z0-T

- Extended temperature range
- 10 mm flush
- Two wire, normally open contact



Dimensions



Technical Data

General specifications

Switching function		Normally open (NO)
Output type		Two-wire
Rated operating distance	s_n	10 mm
Installation		flush
Output polarity		DC
Assured operating distance	s_a	0 ... 8.1 mm
Actuating element		mild steel, e. g. 1.0037, SR235JR (formerly St37-2) 30 mm x 30 mm x 1 mm
Reduction factor r_{Al}		0.4
Reduction factor r_{Cu}		0.3
Reduction factor r_{304}		0.7
Reduction factor r_{Brass}		0.4
Output type		2-wire

Nominal ratings

Installation conditions		
B		25 mm
C		16 mm
F		37 mm
Operating voltage	U_B	15 ... 30 V

Release date: 2025-01-10 Date of issue: 2025-01-10 Filename: 236495_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data

Switching frequency	f	0 ... 300 Hz
Hysteresis	H	0.05 ... 2.2 mm
Reverse polarity protection		reverse polarity-conductive
Short-circuit protection		no
Overload resistance		no
Wire breakage protection		yes
Inductive overvoltage protection		yes
Surge suppression		yes
Ripple		10 %
Voltage drop	U _d	≤ 8 V
Repeat accuracy	R	0.3 mm
Operating current	I _L	2 ... 25 mA
Lowest operating current	I _m	2 mA
No-load supply current	I ₀	≤ 1.5 mA
Time delay before availability	t _v	≤ 40 ms
Switching state indicator		LED, yellow
Functional safety related parameters		
Mission Time (T _M)		20 a
Diagnostic Coverage (DC)		0 %
Compliance with standards and directives		
Standard conformity		
Standards		EN IEC 60947-5-2
Approvals and certificates		
CCC approval		CCC approval / marking not required for products rated ≤36 V
Ambient conditions		
Ambient temperature		-25 ... 100 °C (-13 ... 212 °F)
Storage temperature		-40 ... 100 °C (-40 ... 212 °F)
Mechanical specifications		
Connection type		cable
Housing material		brass, nickel-plated
Sensing face		PBT
Degree of protection		IP67
Cable		
Wire end ferrules		yes
Cable diameter		4.5 mm ± 0.15 mm
Bending radius		> 10 x cable diameter
Material		PUR
Color		black
Number of cores		3
Core cross section		0.25 mm ²
Length	L	2 m
Mass		145 g
Dimensions		
Length		54 mm
Diameter		30 mm

Release date: 2025-01-10 Date of issue: 2025-01-10 Filename: 236495_eng.pdf

Connection

