



# Inductive sensor NBN12-18GM50-EI-M1



- 12 mm non-flush
- Extended temperature range  
-40 ... +85 °C
- Digital current output
- E1-Type approval



## Dimensions



## Technical Data

### General specifications

|                              |       |                                                                             |
|------------------------------|-------|-----------------------------------------------------------------------------|
| Output type                  |       | Digital current output                                                      |
| Rated operating distance     | $s_n$ | 12 mm                                                                       |
| Installation                 |       | non-flush                                                                   |
| Output polarity              |       | DC                                                                          |
| Assured operating distance   | $s_a$ | 0 ... 9.72 mm                                                               |
| Actuating element            |       | mild steel, e. g. 1.0037, SR235JR (formerly St37-2)<br>36 mm x 36 mm x 1 mm |
| Reduction factor $r_{Al}$    |       | 0.45                                                                        |
| Reduction factor $r_{Cu}$    |       | 0.4                                                                         |
| Reduction factor $r_{304}$   |       | 0.7                                                                         |
| Reduction factor $r_{Brass}$ |       | 0.5                                                                         |
| Output type                  |       | 3-wire                                                                      |

### Nominal ratings

|                     |       |               |
|---------------------|-------|---------------|
| Operating voltage   | $U_B$ | 9 ... 30 V DC |
| Switching frequency | $f$   | 0 ... 1000 Hz |
| Hysteresis          | $H$   | 2 ... 15 %    |

Release date: 2025-01-10 Date of issue: 2025-01-10 Filename: 283416-0007\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**

## Technical Data

|                                                 |       |                                                                   |
|-------------------------------------------------|-------|-------------------------------------------------------------------|
| Reverse polarity protection                     |       | reverse polarity protected                                        |
| Short-circuit protection                        |       | yes                                                               |
| Temperature drift                               |       | ≤ 10 %                                                            |
| Time delay before availability                  | $t_v$ | ≤ 5 ms                                                            |
| Load resistor                                   |       | 100 ... 250 Ohm                                                   |
| Switching state indicator                       |       | LED, yellow                                                       |
| <b>Functional safety related parameters</b>     |       |                                                                   |
| MTTF <sub>d</sub>                               |       | 1535 a                                                            |
| Mission Time (T <sub>M</sub> )                  |       | 20 a                                                              |
| Diagnostic Coverage (DC)                        |       | 0 %                                                               |
| <b>Digital output</b>                           |       |                                                                   |
| Output value                                    |       | object detected: 10 mA ± 1 mA<br>object not detected: 5 mA ± 1 mA |
| <b>Compliance with standards and directives</b> |       |                                                                   |
| Standard conformity                             |       |                                                                   |
| Standards                                       |       | EN IEC 60947-5-2                                                  |
| <b>Approvals and certificates</b>               |       |                                                                   |
| UL approval                                     |       | cULus Listed, General Purpose, Class 2 Power Source               |
| E1 Type approval                                |       | 10R-04                                                            |
| <b>Ambient conditions</b>                       |       |                                                                   |
| Ambient temperature                             |       | -40 ... 85 °C (-40 ... 185 °F)                                    |
| Storage temperature                             |       | -40 ... 85 °C (-40 ... 185 °F)                                    |
| <b>Mechanical specifications</b>                |       |                                                                   |
| Connection type                                 |       | cable                                                             |
| Housing material                                |       | brass, nickel-plated                                              |
| Sensing face                                    |       | PBT                                                               |
| Degree of protection                            |       | IP68 / IP69K                                                      |
| Cable                                           |       |                                                                   |
| Wire end ferrules                               |       | yes                                                               |
| Cable diameter                                  |       | 4.3 mm ± 0.1 mm                                                   |
| Bending radius                                  |       | > 10 x cable diameter                                             |
| Material                                        |       | PUR                                                               |
| Color                                           |       | black                                                             |
| Number of cores                                 |       | 3                                                                 |
| Core cross section                              |       | 0.34 mm <sup>2</sup>                                              |
| Length                                          | L     | 2 m                                                               |
| Mass                                            |       | 97 g                                                              |
| Dimensions                                      |       |                                                                   |
| Length                                          |       | 50 mm                                                             |
| Diameter                                        |       | 18 mm                                                             |
| <b>General information</b>                      |       |                                                                   |
| Scope of delivery                               |       | 2 self locking nuts in scope of delivery                          |

## Connection



## Characteristic Curve

