


# Reflector REF-H32G-2



- Specially designed to detect films and transparent plastics with polarization-modifying properties in conjunction with sensors from the R100, R101, and R103 series for detecting clear glass
- With surface mounted polarization filter
- Mounting holes for simple installation



## **Dimensions**



## **Technical Data**

General specifications	
Construction type	hexagonal
Ambient conditions	
Ambient temperature	-20 60 °C (-4 140 °F)
Mechanical specifications	
Material	PMMA/ABS
Dimensions	55 mm x 25 mm x 9 mm
Height	55 mm
Width	25 mm
Mounting	mounting holes

#### **Operation instructions:**

- When aligning the system, the sensor Teach-in function should be used. In rare cases, however, manual adjustment of the sensitivity via the sensor may be necessary.
  - This applies, for example, to CD cases, on which the signal attenuation near to the edges is much stronger than in the centre. A Teach-in operation would match the response threshold at the strongly attenuated edge region. The detection of the poorly absorbing centre area of the CD case would then become questionable.
  - In such cases a solution is found by manually adjusting the sensitivity.
- For a sure detection of films with extremely inhomogeneous polarisation characteristics, the reflector must be mounted as close as possible to the film.

#### Notes on use and cleaning:

- Not suitable for regular outside use or in wet / damp areas.
- Clean with a damp cloth. Do not use aggressive or scouring cleaning agents.