


## Inductive sensor


### NBN12-18GM50-A0-M1



- 12 mm non-flush
- Increased operating distance
- Extended temperature range  
-40 ... +85 °C
- With increased sealing, protection class  
IP68 / IP69K
- E1-Type approval



## Dimensions



## Technical Data

### General specifications

|                              |       |                                                                             |
|------------------------------|-------|-----------------------------------------------------------------------------|
| Switching function           |       | complementary                                                               |
| Output type                  |       | NPN                                                                         |
| Rated operating distance     | $s_n$ | 12 mm                                                                       |
| Installation                 |       | non-flush                                                                   |
| Output polarity              |       | DC                                                                          |
| Assured operating distance   | $s_a$ | 0 ... 9.72 mm                                                               |
| Actuating element            |       | mild steel, e. g. 1.0037, SR235JR (formerly St37-2)<br>36 mm x 36 mm x 1 mm |
| Reduction factor $r_{Al}$    |       | 0.5                                                                         |
| Reduction factor $r_{Cu}$    |       | 0.45                                                                        |
| Reduction factor $r_{304}$   |       | 0.7                                                                         |
| Reduction factor $r_{Brass}$ |       | 0.5                                                                         |
| Output type                  |       | 4-wire                                                                      |

### Nominal ratings

|                     |       |               |
|---------------------|-------|---------------|
| Operating voltage   | $U_B$ | 7 ... 30 V    |
| Switching frequency | $f$   | 0 ... 1200 Hz |

Release date: 2025-01-10 Date of issue: 2025-01-10 Filename: 293454-0048\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

## Technical Data

|                                                 |       |                                                                    |
|-------------------------------------------------|-------|--------------------------------------------------------------------|
| Hysteresis                                      | H     | typ. 5%                                                            |
| Reverse polarity protection                     |       | reverse polarity protected                                         |
| Short-circuit protection                        |       | pulsing                                                            |
| Voltage drop                                    | $U_d$ | $\leq 2$ V                                                         |
| Operating current                               | $I_L$ | 0 ... 200 mA                                                       |
| Off-state current                               | $I_r$ | 0 ... 0.5 mA typ. 4 $\mu$ A at 25 °C                               |
| No-load supply current                          | $I_0$ | $\leq 10$ mA                                                       |
| Time delay before availability                  | $t_v$ | $\leq 100$ ms                                                      |
| Switching state indicator                       |       | LED, yellow                                                        |
| <b>Functional safety related parameters</b>     |       |                                                                    |
| MTTF <sub>d</sub>                               |       | 1484 a                                                             |
| Mission Time (T <sub>M</sub> )                  |       | 20 a                                                               |
| Diagnostic Coverage (DC)                        |       | 0 %                                                                |
| <b>Compliance with standards and directives</b> |       |                                                                    |
| Standard conformity                             |       |                                                                    |
| Standards                                       |       | EN IEC 60947-5-2                                                   |
| <b>Approvals and certificates</b>               |       |                                                                    |
| UL approval                                     |       | cULus Listed, General Purpose, Class 2 Power Source                |
| CCC approval                                    |       | CCC approval / marking not required for products rated $\leq 36$ V |
| E1 Type approval                                |       | 10R-04                                                             |
| <b>Ambient conditions</b>                       |       |                                                                    |
| Ambient temperature                             |       | -40 ... 85 °C (-40 ... 185 °F)                                     |
| Storage temperature                             |       | -40 ... 85 °C (-40 ... 185 °F)                                     |
| <b>Mechanical specifications</b>                |       |                                                                    |
| Connection type                                 |       | cable                                                              |
| Housing material                                |       | brass, nickel-plated                                               |
| Sensing face                                    |       | PBT                                                                |
| Degree of protection                            |       | IP68 / IP69K                                                       |
| Cable                                           |       |                                                                    |
| Wire end ferrules                               |       | yes                                                                |
| Cable diameter                                  |       | 4.3 mm $\pm$ 0.1 mm                                                |
| Bending radius                                  |       | > 10 x cable diameter                                              |
| Material                                        |       | PUR                                                                |
| Color                                           |       | black                                                              |
| Number of cores                                 |       | 4                                                                  |
| Core cross section                              |       | 0.34 mm <sup>2</sup>                                               |
| Length                                          | L     | 2 m                                                                |
| Mass                                            |       | 90 g                                                               |
| Dimensions                                      |       |                                                                    |
| Length                                          |       | 50 mm                                                              |
| Diameter                                        |       | 18 mm                                                              |
| <b>General information</b>                      |       |                                                                    |
| Scope of delivery                               |       | 2 self locking nuts in scope of delivery                           |

## Connection



Technical Features

Mains-borne interference in accordance with ISO 7637-2:

|                   |     |     |     |     |     |     |
|-------------------|-----|-----|-----|-----|-----|-----|
| Pulse             | 1   | 2a  | 2b  | 3a  | 3b  | 4   |
| Severity level    | III | III | III | III | III | III |
| Failure criterion | A   | A   | C   | A   | A   | C   |

|                |                        |
|----------------|------------------------|
| EN 61000-4-2:  | CD: 8 kV / AD: 15 kV   |
| Severity level | IV IV                  |
| EN 61000-4-3:  | 36 V/m (80...2500 MHz) |
| Severity level | IV                     |
| EN 61000-4-4:  | 2 kV                   |
| Severity level | III                    |
| EN 61000-4-6:  | 30 V (0.01...80 MHz)   |
| Severity level | III                    |
| EN 55011:      | Class A                |

Release date: 2025-01-10 Date of issue: 2025-01-10 Filename: 293454-0048\_eng.pdf