




## Inductive analog sensor NBB5-18GM60-I-V1

- Inductive analog sensor
- Output 4 mA ... 20 mA
- Flush mounting



### Dimensions



### Technical Data

#### General specifications

|                 |                       |
|-----------------|-----------------------|
| Output type     | Analog current output |
| Installation    | flush                 |
| Output polarity | DC                    |
| Measuring range | 1 ... 5 mm            |
| Output type     | 3-wire                |

#### Nominal ratings

|                             |       |                             |
|-----------------------------|-------|-----------------------------|
| Operating voltage           | $U_B$ | 10 ... 30 V DC typ. 20 V DC |
| Reverse polarity protection |       | yes                         |
| Repeat accuracy             |       | 0 ... 80 $\mu$ m            |
| No-load supply current      | $I_0$ | $\leq 12$ mA                |

#### Analog output

|                                |                                      |
|--------------------------------|--------------------------------------|
| Output type                    | 4 ... 20 mA                          |
| Slope of output characteristic | 4 mA / mm                            |
| Linearity error                | $\leq \pm 5$ % of full-scale value   |
| Load resistor                  | $\leq 1000 \Omega$ typ. 500 $\Omega$ |
| Rate of current rise           |                                      |
| 4 ... 20 mA                    | max. 30.9 A/s                        |
| 20 ... 4 mA                    | max. 11.1 A/s                        |

Release date: 2025-03-12 Date of issue: 2025-03-12 Filename: 303099\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**


Technical Data

|                                          |                                                                                      |
|------------------------------------------|--------------------------------------------------------------------------------------|
| Recovery time                            | 1 ... 10 ms , typ. 5 ms                                                              |
| Adjustment tolerance zero point          | $\leq \pm 5 \%$ of full-scale value                                                  |
| Temperature drift                        | $\leq \pm 0.15 \%$ /K of full-scale value                                            |
| Residual ripple                          | $\pm 125 \mu\text{A}$                                                                |
| Compliance with standards and directives |                                                                                      |
| Standard conformity                      |                                                                                      |
| Standards                                | EN IEC 60947-5-2                                                                     |
| Approvals and certificates               |                                                                                      |
| UL approval                              | cULus Listed, Class 2 Power Source                                                   |
| CCC approval                             | CCC approval / marking not required for products rated $\leq 36 \text{ V}$           |
| Ambient conditions                       |                                                                                      |
| Ambient temperature                      | $-25 \dots 70 \text{ }^{\circ}\text{C}$ ( $-13 \dots 158 \text{ }^{\circ}\text{F}$ ) |
| Mechanical specifications                |                                                                                      |
| Connection type                          | Connector plug                                                                       |
| Housing material                         | brass, nickel-plated                                                                 |
| Sensing face                             | PBT                                                                                  |
| Degree of protection                     | IP67                                                                                 |
| Connector                                |                                                                                      |
| Threading                                | M12 x 1                                                                              |
| Number of pins                           | 3                                                                                    |
| Dimensions                               |                                                                                      |
| Length                                   | 75 mm                                                                                |
| Diameter                                 | 18 mm                                                                                |

Connection



Connection Assignment




Wire colors in accordance with EN 60947-5-2

|   |    |         |
|---|----|---------|
| 1 | BN | (brown) |
| 2 | WH | (white) |
| 3 | BU | (blue)  |
| 4 | BK | (black) |

Release date: 2025-03-12 Date of issue: 2025-03-12 Filename: 303099\_eng.pdf

Characteristic Curve

Output characteristics



Reduction factor

