


# Inductive sensor


## NBN3-6,5M30-E2



- 3 mm non-flush
- Increased operating distance
- Extended temperature range  
-40 ... +85 °C



### Dimensions



### Technical Data

| General specifications              |                |                                                                           |
|-------------------------------------|----------------|---------------------------------------------------------------------------|
| Switching function                  |                | Normally open (NO)                                                        |
| Output type                         |                | PNP                                                                       |
| Rated operating distance            | s <sub>n</sub> | 3 mm                                                                      |
| Installation                        |                | non-flush                                                                 |
| Output polarity                     |                | DC                                                                        |
| Assured operating distance          | s <sub>a</sub> | 0 ... 2.43 mm                                                             |
| Actuating element                   |                | mild steel, e. g. 1.0037, SR235JR (formerly St37-2)<br>9 mm x 9 mm x 1 mm |
| Reduction factor r <sub>Al</sub>    |                | 0.55                                                                      |
| Reduction factor r <sub>Cu</sub>    |                | 0.5                                                                       |
| Reduction factor r <sub>304</sub>   |                | 0.75                                                                      |
| Reduction factor r <sub>Brass</sub> |                | 0.55                                                                      |
| Output type                         |                | 3-wire                                                                    |
| Nominal ratings                     |                |                                                                           |
| Operating voltage                   | U <sub>B</sub> | 5 ... 30 V                                                                |
| Switching frequency                 | f              | 0 ... 4500 Hz                                                             |
| Hysteresis                          | H              | typ. 5%                                                                   |
| Reverse polarity protection         |                | reverse polarity protected                                                |
| Short-circuit protection            |                | pulsing                                                                   |
| Voltage drop                        | U <sub>d</sub> | ≤ 1.5 V                                                                   |
| Operating current                   | I <sub>L</sub> | 0 ... 100 mA                                                              |
| Off-state current                   | I <sub>r</sub> | 0 ... 0.2 mA                                                              |
| No-load supply current              | I <sub>0</sub> | ≤ 10 mA                                                                   |

Release date: 2025-02-27 Date of issue: 2025-02-27 Filename: 304615-0110\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**

## Technical Data

|                                                 |       |                                                                            |
|-------------------------------------------------|-------|----------------------------------------------------------------------------|
| Time delay before availability                  | $t_v$ | $\leq 100 \text{ ms}$                                                      |
| Switching state indicator                       |       | LED, yellow                                                                |
| <b>Functional safety related parameters</b>     |       |                                                                            |
| MTTF <sub>d</sub>                               |       | 960 a                                                                      |
| Mission Time (T <sub>M</sub> )                  |       | 20 a                                                                       |
| Diagnostic Coverage (DC)                        |       | 0 %                                                                        |
| <b>Compliance with standards and directives</b> |       |                                                                            |
| Standard conformity                             |       |                                                                            |
| Standards                                       |       | EN IEC 60947-5-2                                                           |
| <b>Approvals and certificates</b>               |       |                                                                            |
| UL approval                                     |       | cULus Listed, General Purpose                                              |
| CCC approval                                    |       | CCC approval / marking not required for products rated $\leq 36 \text{ V}$ |
| <b>Ambient conditions</b>                       |       |                                                                            |
| Ambient temperature                             |       | -40 ... 85 °C (-40 ... 185 °F)                                             |
| Storage temperature                             |       | -40 ... 85 °C (-40 ... 185 °F)                                             |
| <b>Mechanical specifications</b>                |       |                                                                            |
| Connection type                                 |       | cable                                                                      |
| Housing material                                |       | brass, nickel-plated                                                       |
| Sensing face                                    |       | LCP                                                                        |
| Degree of protection                            |       | IP65 / IP66 / IP67                                                         |
| <b>Cable</b>                                    |       |                                                                            |
| Wire end ferrules                               |       | yes                                                                        |
| Cable diameter                                  |       | 3.5 mm $\pm$ 0.1 mm                                                        |
| Bending radius                                  |       | > 10 x cable diameter                                                      |
| Material                                        |       | PVC                                                                        |
| Color                                           |       | black                                                                      |
| Number of cores                                 |       | 3                                                                          |
| Core cross section                              |       | 0.14 mm <sup>2</sup>                                                       |
| Length                                          | L     | 2 m                                                                        |
| <b>Dimensions</b>                               |       |                                                                            |
| Length                                          |       | 30 mm                                                                      |
| Diameter                                        |       | 6.5 mm                                                                     |

## Connection

