


Receptacles

V1S-K-PG9P-90




- Plastic version
- Front/screw mounting
- M12 plug can be mounted in any position

Receptacles, M12/PG9, 4-pin; plastic version



Dimensions



Technical Data

General specifications

Connector 1	
Connection	plug
Construction type	M12
Style	straight
Locking	screw connection
Number of pins	4
Coding	A-coded
Connector 2	
Connection	cable end

Electrical specifications

Operating voltage	U_B	max. 250 V AC/DC
Operating current	I_B	max. 4 A
Volume resistance		< 5 mΩ

Conformity

Degree of protection	EN 60529
Plug connection	connector M12 x 1 : IEC 61076-2-101

Ambient conditions

Ambient temperature	-25 ... 80 °C (-13 ... 176 °F)
---------------------	--------------------------------

Mechanical specifications

Degree of protection	IP67 when sealing with O-Ring
----------------------	-------------------------------

Release date: 2025-01-10 Date of issue: 2025-01-10 Filename: 317057_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data

Connection		Single strand leads with connector sleeves	
Cable			
Number of cores		4	
Core cross section			0.25 mm²
Cores color		Core 1: brown Core 2: white Core 3: blue Core 4: black	
Length	L	80 mm	
Installation		Front mounting PG9	
Mass		10.72 g	
Material			
Plug connector			
Screw connection		plastic	
Body		plastic	
Seal		NBR	
Contact surface			gold plated (Au)
Cable			
Core insulation			PVC
General information			
Scope of delivery			locknut included


Connection Assignment



1	■		BN
2	■		WH
3	■		BU
4	■		BK

Release date: 2025-01-10 Date of issue: 2025-01-10 Filename: 317057_eng.pdf

Mounting



	A	B	C	D	E	F
M8	7.1 ^{+0.1}	Ø 8.2 ^{+0.1}	2 - 4 mm	-	M8x0.5	2 - 4 mm
M12	11 ^{+0.1}	Ø 12.2 ^{+0.1}	< 4 mm	-	M12x1	< 4.5 mm
M16	13.5 ^{+0.1}	Ø 16.1	< 4.5 mm	Ø 17 ^{+0.2}	M16x1.5	> 2.5 mm
M20	13.5 ^{+0.1}	Ø 20.1	-	Ø 20 ^{+0.2}	M20x1.5	< 6 mm
PG9	13.5 ^{+0.1}	Ø 15.3 ^{+0.1}	< 4.5 mm	Ø 16	PG9	> 2.5 mm
PG13.5	18.8 ^{+0.1}	Ø 20.5 ^{+0.1}	-	Ø 22 ^{±0.1}	PG13.5	-

Release date: 2025-01-10 Date of issue: 2025-01-10 Filename: 317057_eng.pdf