

Inductive sensor


NJ10-30GK-SN-15M



- 10 mm flush
- Usable up to SIL 3 acc. to IEC 61508
- Degree of protection IP68
- ATEX-/IECEx-approvals for zone 0/1/20/21 (Ex i)
- ATEX-/IECEx-approvals for zone 2/22 (Ex ec/tc)
- 15 m connection cable



Dimensions



Technical Data

Release date: 2025-06-13 Date of issue: 2025-06-17 Filename: 70133152_eng.pdf

| General specifications | | |
|------------------------------|--|--------------------------------------|
| Switching function | Normally closed (NC) | |
| Output type | NAMUR with safety function | |
| Rated operating distance | s_n | 10 mm |
| Installation | flush | |
| Assured operating distance | s_a | 0 ... 8.1 mm |
| Reduction factor r_{AI} | 0.4 | |
| Reduction factor r_{Cu} | 0.3 | |
| Reduction factor r_{304} | 0.85 | |
| Safety Integrity Level (SIL) | up to SIL3 acc. to IEC 61508 Danger! In safety-related applications the sensor must be operated with a qualified fail safe interface from Pepperl+Fuchs, such as KFD2-SH-EX1. Consider the "exida Functional Safety Assessment" document which is available on www.pepperl-fuchs.com as an integral part of this product's documentation. | |
| Output type | 2-wire | |
| Nominal ratings | | |
| Nominal voltage | U_o | 8.2 V (R_i approx. 1 k Ω) |
| Switching frequency | f | 0 ... 300 Hz |
| Current consumption | | |

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data

| | | |
|---|--|------|
| Measuring plate not detected | ≥ 3 mA | |
| Measuring plate detected | ≤ 1 mA | |
| Functional safety related parameters | | |
| Safety Integrity Level (SIL) | SIL 3 | |
| MTTF _d | 11850 a | |
| Mission Time (T _M) | 20 a | |
| Diagnostic Coverage (DC) | 0 % | |
| Compliance with standards and directives | | |
| Standard conformity | | |
| NAMUR | EN 60947-5-6:2000 IEC 60947-5-6:1999 | |
| Standards | EN IEC 60947-5-2 | |
| Approvals and certificates | | |
| IECEx approval | | |
| Equipment protection level Ga | IECEx PTB 11.0092X | |
| Equipment protection level Gb | IECEx PTB 11.0092X | |
| Equipment protection level Gc (ec) | IECEx TUR 21.0017X | |
| Equipment protection level Da | IECEx PTB 11.0092X | |
| Equipment protection level Dc (tc) | IECEx TUR 21.0018X | |
| Equipment protection level Mb | IECEx PTB 11.0092X | |
| ATEX approval | | |
| Equipment protection level Ga | PTB 00 ATEX 2049 X | |
| Equipment protection level Gb | PTB 00 ATEX 2049 X | |
| Equipment protection level Gc (ec) | TÜV 20 ATEX 8523 X | |
| Equipment protection level Da | PTB 00 ATEX 2049 X | |
| Equipment protection level Dc (tc) | TÜV 20 ATEX 8524 X | |
| UL approval | cULus Listed, General Purpose | |
| Ordinary Location | E87056 | |
| Hazardous Location | E501628 | |
| Control drawing | 116-0454 | |
| CCC approval | | |
| Hazardous Location | 2020322315002308 2024322315005947 2024322315005860 | |
| Ambient conditions | | |
| Ambient temperature | -40 ... 100 °C (-40 ... 212 °F) | |
| Mechanical specifications | | |
| Connection type | cable | |
| Housing material | Crastin (PBT), black | |
| Sensing face | Crastin (PBT), black | |
| Degree of protection | IP68 | |
| Cable | | |
| Cable diameter | 6 mm \pm 0.2 mm | |
| Bending radius | > 10 x cable diameter | |
| Material | silicone | |
| Core cross section | 0.75 mm ² | |
| Length | L | 15 m |
| Dimensions | | |
| Length | 40 mm | |
| Diameter | 30 mm | |
| General information | | |
| Scope of delivery | Supplied with 2 nuts | |
| Use in the hazardous area | see instruction manuals | |

Connection Assignment



Application

Danger!

 In safety-related applications the sensor must be operated with a qualified fail safe interface from Pepperl+Fuchs, such as KFD2-SH-EX1.

Consider the "exida Functional Safety Assessment" document which is available on www.pepperl-fuchs.com as an integral part of this product's documentation.