



Inductive sensor NBB10-30GKK-WO



■ 10 mm flush



Dimensions



Technical Data

General specifications

Switching function	Normally closed (NC)	
Output type	Two-wire	
Rated operating distance	s_n	10 mm
Installation	flush	
Output polarity	AC	
Assured operating distance	s_a	0 ... 8.1 mm
Reduction factor r_{Al}	0.33	
Reduction factor r_{Cu}	0.28	
Reduction factor r_{304}	0.82	
Output type	2-wire	

Nominal ratings

Operating voltage	U_B	20 ... 250 V
Switching frequency	f	0 ... 20 Hz

Release date: 2025-06-06 Date of issue: 2025-06-06 Filename: 802846_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Hysteresis	H	typ. 5 %
Short-circuit protection		no
Voltage drop	U _d	≤ 8 V
Momentary current (20 ms, 0.1 Hz)		0 ... 1600 mA
Operating current	I _L	1.5 ... 200 mA
No-load supply current	I ₀	≤ 1.7 mA
Time delay before availability	t _v	≤ 20 ms
Compliance with standards and directives		
Standard conformity		
Standards		EN IEC 60947-5-2
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
CCC approval		Certified by China Compulsory Certification (CCC)
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		terminal compartment
Core cross section		up to 2.5 mm ²
Housing material		PBT
Sensing face		PBT
Degree of protection		IP67
Dimensions		
Length		115 mm
Diameter		30 mm
Note		1) In the temperature range below 0 °C, permissible operating voltage U _b 80...253 V Safety fuse ≤ 0.8 A (quick-blow) according to IEC 60127-2 Sheet 1 Recommendation: after a short circuit, check that the device is functioning correctly.

Connection



Release date: 2025-06-06 Date of issue: 2025-06-06 Filename: 802846_eng.pdf