


Inductive sensor


NBB15-30GM50-WS-10M



- Basic series
- 15 mm flush
- 2-wire AC



Dimensions



Technical Data

General specifications			
Rated operating distance	s_n	15 mm	
Installation		quasi flush	
Output polarity		AC	
Assured operating distance	s_a	0 ... 12.15 mm	
Actual operating distance	s_r	13.5 ... 16.5 mm	
Reduction factor r_{AI}		0.33	
Reduction factor r_{Cu}		0.28	
Reduction factor r_{304}		0.81	
Output type		2-wire	
Nominal ratings			
Operating voltage	U_B	20 ... 253 V	
Switching frequency	f	0 ... 20 Hz	
Hysteresis	H	1 ... 10 % typ. 5 %	
Reverse polarity protection		reverse polarity tolerant	
Voltage drop	U_d	< 5 V ($I_L > 50$ mA); < 8 V ($I_L < 50$ mA)	

Release date: 2025-06-04 Date of issue: 2025-06-04 Filename: 806441_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Momentary current (20 ms, 0.1 Hz)		0 ... 1600 mA
Operating current	I _L	5 ... 200 mA
Off-state current	I _r	0 ... 1.7 mA
Operating voltage indicator		LED, green
Switching state indicator		LED, yellow
Compliance with standards and directives		
Standard conformity		
Standards		EN IEC 60947-5-2
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
CCC approval		Certified by China Compulsory Certification (CCC)
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		cable
Housing material		brass, nickel-plated
Sensing face		PBT
Degree of protection		IP67
Cable		
Wire end ferrules		yes
Cable diameter		6.4 mm ± 0.2 mm
Bending radius		> 10 x cable diameter
Material		PVC
Color		grey
Number of cores		3
Core cross section		0.75 mm ²
Length	L	10 m
Mass		752 g
Dimensions		
Length		50 mm
Diameter		30 mm
Note		1) In the temperature range below 0 °C, permissible operating voltage U _b 80...253 V Safety fuse ≤ 0.3 A (quick-blow) according to IEC 60127-2 Sheet 1 Recommendation: after a short circuit, check that the device is functioning correctly.

Connection



Release date: 2025-06-04 Date of issue: 2025-06-04 Filename: 806441_eng.pdf

Mounting

Installation conditions

