




Magnetic field sensor 50FY41-V4A-50

- Hall Effect Sensor
- Sensing range 2.5 mm
- 4-wire DC



Dimensions



Technical Data

General specifications

Switching function		Normally open (NO)
Output type		PNP/NPN
Rated operating distance	s_n	2.5 mm at 0 mm offset, 1.3 mm at 3.5 mm offset, 0 mm at 4.0 mm offset
Installation		non-flush
Output polarity		DC
Output type		4-wire

Nominal ratings

Operating voltage	U_B	10 ... 12 V
Short-circuit protection		NO
Voltage drop	U_d	7 V @ 10 K load, 12 V supply
Operating current	I_L	0.5 mA
Current consumption		30 mA

Compliance with standards and directives

Standard conformity	
---------------------	--

Release date: 2025-02-27 Date of issue: 2025-02-28 Filename: 915924_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Standards	IEC 60947-5-2:2012 IEC 60947-5-3:2013 IEC 61236-3-1:2008	
Approvals and certificates		
CE conformity		2014/30/EU
UL approval		cULus Listed, General Purpose
Ambient conditions		
Ambient temperature		-40 ... 100 °C (-40 ... 212 °F)
Mechanical specifications		
Connection type		cable
Housing material		316 stainless steel
Sensing face		316 stainless steel
Degree of protection		IP69K
Cable		
Wire end ferrules		yes
Cable diameter		6.35 mm ± 0.4 mm
Bending radius		> 10 x cable diameter
Material		PVC
Color		yellow
Number of cores		4
Core cross section		0.34 mm²
Length	L	15 m
Dimensions		
Width		39 mm
Depth		12.7 mm
Length		39 mm
Note	Only approved for use with FYQLA1-140R-3 and KE5D2-6H/2R-S Use only with actuator 52FY31-V4A	

Connection



Release date: 2025-02-27 Date of issue: 2025-02-28 Filename: 915924_eng.pdf