

PNOZ s6 24VDC 3 n/o 1 n/c

750106



Safety relay (standalone) Inputs: 1 N/O, 1 N/C per pushbutton Outputs: 3 N/O, 1 N/C, 1 semiconductor. UB 24 V DC, width: 22.5 mm, plug-in terminals of screw type Two-hand control device, monitoring the simultaneity of a two-hand pushbutton.

Dati tecnici

Omologazioni:	CE;cULus Listed;TÜV;KOSHA;CCC
Possibilità applicative:	Controllo bimanuale tipo III C
Corrente max in DC1:	6.0 A
Tensione in AC1:	240 V
Tipo morsetto:	Morsetto a vite
Tipo morsetto:	estraibile
Categoria di arresto:	0
Norme:	EN 574 TYP III C;EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Modalità operative:	bicanale;Riconoscimento del cortocircuito
Tensione di alimentazione (V):	24,0
Larghezza:	22.5 mm
Altezza:	98.0 mm
Profondità:	120.0 mm
Peso lordo:	195 g
Peso netto:	185 g
Temperatura ambiente:	-10 - 55 °C

Accessori opzionali



750004

PNOZ s Setscrew terminals 22,5mm



750010

PNOZ s terminator plug (10 pieces)