

BORG

Apparecchio LED a parete per esterno (IP54). Struttura in pressofusione di alluminio verniciato con polveri poliestere a elevata resistenza ai raggi ultravioletti e alla corrosione, diffusore in vetro temperato.

Alimentatore LED integrato.

Disponibile in due finiture e due temperature colore (3000K e 4000K).

Disponibili giunti certificati IP68 per la realizzazione delle connessioni elettriche con barriera anticondensa.

Wall outdoor (IP54) LED luminaire. Die-cast aluminium body, painted with polyester powders, highly resistant to UV rays and corrosion, tempered glass diffuser.

Integrated LED driver.

Available in two finishes (white and anthracite) and in two gradations (3000K and 4000K).



IP68 linear connectors for moisture protection and anti-condensation linear joints are available.



MONOEMISSIONE DIRECT LIGHT





Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
BOR001XX	3000K	310	1x3W	65 x 88 x 40
BOR003XX	4000K	330	1x3W	65 x 88 x 40



BIEMISSIONE DIRECT-INDIRECT LIGHT



Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
BOR002XX	3000K	310+310	2x3W	43 x 125 x 90
BOR004XX	4000K	330+330	2x3W	43 x 125 x 90



Finiture Finishes



B



AN

Accessori Accessories



connessione IP68
IP68 connection

p.897