



GHEBI

Apparecchio biemissione a parete per esterno (IP54) a LED o con attacco G9 che consente di montare lampadina LED (max 5W).

Struttura in pressofusione di alluminio verniciato con polveri poliestere ad elevata resistenza ai raggi ultravioletti e alla corrosione, proposta in due finiture (grigio e nero).

Versione LED con fascio di luce a 37°, alimentatore LED integrato; disponibile in due temperature colore (3000K e 4000K).


Disponibili giunti certificati IP68 per la realizzazione delle connessioni elettriche, sicure, durevoli e con barriera anticondensa.

Outdoor (IP54) wall luminaire direct/indirect light emission with LED lamp holder or G9 lamp holder allows mounting the LED lamp (max 5W).



Die-cast aluminium body, painted with polyester powders, highly resistant to UV rays and corrosion, available in two finishes (grey and black).

LED version with light beam 37°, integrated LED drive and available in two gradations (3000K and 4000K).


IP68 linear connectors for moisture protection and anti-condensation linear joints are available.



Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
GHE001XX	3000K	1180	2x7W	Ø80 x 160
GHE002XX	4000K	1240	2x7W	Ø80 x 160



Codice Code		Potenza Wattage	Dimensioni mm Dimensions mm
GHE003XX	G9	1x5W LED max	Ø115 x 85



Finiture Finishes



GR



N

Accessori Accessories


connessione IP68
IP68 connection

p.897