



LINK

Faretto LED ad incasso per esterno, da terra, calpestabile (max. 500Kg). Corpo in alluminio con vetro temperato e cassaforma in dotazione. Ghiera e viti di fissaggio in acciaio INOX AISI 304, guarnizioni in silicone per garantire un alto livello di protezione (IP67). Alimentatore LED integrato. Disponibile nella versione tonda e quadrata, due dimensioni e relative potenze e in due temperature colore (3000K e 4000K). Disponibili giunti certificati IP68 per la realizzazione delle connessioni elettriche, sicure, durevoli e con barriera anticondensa.




LED outdoor recessed luminaire, walk over (max. 500Kg), ground installation. Aluminium body with tempered glass, supplied with recessed box. AISI304 stainless steel ring nut and fixing screws, silicone gasket to ensure a high protection grade (IP67). Integrated LED driver. Available in round and square versions, in two sizes and related powers, in two gradations (3000K and 4000K). IP68 linear connectors for moisture protection and anti-condensation linear joints are available.



 calpestabile max Kg 500
walk over max Kg 500

 AISI304  LED  30°  CRI≥80  IP67  IK05




Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
LIN001	3000K	90	1W	Ø67 x 117
LIN005	4000K	100	1W	Ø67 x 117
LIN003	3000K	630	7W	Ø125 x 105
LIN006	4000K	680	7W	Ø125 x 105



 calpestabile max Kg 500
walk over max Kg 500

 AISI304  LED  30°  CRI≥80  IP67  IK05

Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
LIN002	3000K	90	1W	67 x 67 x 117
LIN007	4000K	100	1W	67 x 67 x 117
LIN004	3000K	630	7W	125 x 125 x 105
LIN008	4000K	680	7W	125 x 125 x 105



Finiture Finishes



Acciaio AISI304 Stainless steel AISI304

Accessori Accessories



connessione IP68
IP68 connection



cassaforma
inclusa
recessed box
included