

BAZ

Faretto LED ad incasso RGB, con ottica a 50° installabile a parete o soffitto.
Struttura in ottone cromato con lente in vetro, cavo di alimentazione incluso e può essere installato in ambienti con elevata polvere e umidità (IP44).
Necessita di alimentatore LED TS.412 da installare in remoto.
Cassaforma per installazione in muratura da ordinare come accessorio. Disponibili cavi precablati per connessione rapida da ordinare separatamente.


Ceiling and wall RGB LED downlight, 50° beam angle.
Chrome brass body with glass lens, power cable included and thanks to its (IP44) protection degree it is suitable for installation in damp and dusty environments.
Remote LED driver TS.412 to be ordered separately.
Casting box available as accessory to be ordered separately. Pre-wired cables for quick connection are available as accessories to be ordered separately.



Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
8856	RGB	110	2W - 220mA	Ø40 x 45

foro hole

— Ø29 —



MT.8856-1

cavo 3 poli (Rosso-Verde-Blu) precablato con 1 connettore maschio - L:1,5 m
pre-wired 3-pole cable (Red-Green-Blue) with 1 plug connector - L:1,5 m

MT.8856-2

cavo 3 poli (Rosso-Verde-Blu) precablato con 2 connettori maschio - L:1,5 m
pre-wired 3-pole cable (Red-Green-Blue) with 2 plug connectors - L:1,5 m

MT.8856-3


cavo 3 poli (Arancio-Bianco-Nero) precablato con 1 connettore maschio - L:1,5 m
pre-wired 3-pole cable (Orange-White-Black) with 1 plug connector - L:1,5 m

Finiture Finishes



Ottone cromato Chrome brass

Accessori Accessories



TS.412
Kit alimentatore LED e controller
Kit LED driver and controller
p.882



MT.8856
cassaforma per muratura
casting box
Ø60 x 69