

PITT





Apparecchio LED per esterno (IP54) nella versione a parete biemissione e a paletto. Struttura in pressofusione di alluminio verniciato con polveri poliestere a elevata resistenza ai raggi ultravioletti e alla corrosione. Diffusore in policarbonato per un effetto di luce diffusa. La versione a parete può essere installata in verticale o in orizzontale per garantire la migliore luce diffusa con effetto scenografico sulla superficie di installazione. La vesione a paletto, grazie al suo design moderno, minimal ed elegante, si adatta perfettamente allo stile di qualsiasi giardino o cortile esterno.

Outdoor (IP54) LED luminaire available in wall version direct/indirect light or bollard version. Die-cast aluminum structure painted with polyester powders with high resistance to ultraviolet rays and corrosion and polycarbonate diffuser. Wall version can be installed vertically or horizontally to ensure the best diffused light with scenographic light effects. Bollad version, thanks to its modern, minimal and elegant design, it adapts perfectly to the style of any garden or outdoor areas.

PITT

La struttura vuota permette alla luce di creare un'atmosfera piacevole e accogliente. Disponibili in due finiture (antracite e corten). Alimentatore LED integrato. Disponibili giunti certificati IP68 per la realizzazione delle connessioni elettriche, sicure, durevoli e con barriera anticondensa.

The empty structure allows the light to create a pleasant atmosphere. Available in two finishes (anthracite and corten). Integrated LED driver. IP68 linear connectors for moisture protection and anti-condensation linear joints are available.





Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm			
PIT001XX	3000K	600	7W	175 x 120 x 40			





LED CRI≥80 D IP54							
Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm			
PIT002XX	3000K	600	7W	120 x 40 x 650			



Finiture Finishes





Accessori Accessories

.

connessione IP68 IP68 connection

