

Alte prestazioni. High performance.



Faretto LED ad incasso tondo per esterno da terra. Corpo in alluminio con vetro temperato, cassaforma in dotazione. Ghiera e viti di fissaggio in acciaio INOX AISI304, guarnizioni in silicone per garantire un alto livello di protezione (IP65). Alimentatore LED integrato. Disponibile in due temperature colore (3000K e 4000K). Disponibili giunti certificati IP68 per la realizzazione delle connessioni elettriche, sicure, durevoli e con barriera anticondensa.

Outdoor round LED recessed luminaire, ground installation. Aluminium body with tempered glass, recessed box included.


AISI304 stainless steel ring nut and fixing screws, silicone gasket to ensure a high protection grade (IP65). Integrated LED driver. Available in two gradations (3000K and 4000K). IP68 linear connectors for moisture protection and anti-condensation linear joints are available.

SEARCH



AISI304 LED 40° CRI≥90 IP65 IK09

Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
SEA001	3000K	1285	12,6W	Ø135 x 101
SEA002	4000K	1350	12,6W	Ø135 x 101



Finiture Finishes



Acciaio AISI304 Stainless steel AISI304

Accessori Accessories



connessione IP68
IP68 connection

p.897



cassaforma
inclusa
recessed box
included