

WON

Apparecchio LED quadrato per installazione su controsoffitti modulari con struttura a vista (600x600mm) e su cartongesso con apposito accessorio. Dotato di ottica darklight, in alluminio speculare laccato, per ridurre l'abbagliamento e ottenere un ottimo comfort visivo (UGR<16). Adatto per ambienti con videotermini, luoghi di lavoro e uffici. Alimentatore integrato. Disponibile in due temperature colore (3000K e 4000K).

LED recessed square luminaire for installation on false ceilings with exposed structure (600x600mm) and on recessed plasterboard surfaces with related accessories to be ordered separately. Sheet steel body equipped with preanodized aluminium optic to achieve excellent visual comfort and low glare emission (UGR<16). Suitable for VDU workstations, workplaces and offices. On board driver. Available in two gradations (3000K and 4000K).





LED

UGR<16

CRI≥80

IP20

Code Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
WON001	3000K	3460	36W	595 x 595 x 42
WON002	4000K	3640	36W	595 x 595 x 42



Finiture Finishes



Bianco White

Accessori Accessories



WON110ST
Kit staffe montaggio cartongesso
fixing kit brackets for plasterboard recessed installation