



# ENTER

Apparecchio a LED a parete e a plafone per esterno IP65. Corpo in pressofusione di alluminio, verniciato a polveri poliestere ad elevata resistenza ai raggi ultravioletti e alla corrosione; diffusore in vetro temperato satinato.

Parabola riflettente in alluminio, guarnizioni in silicone e viti di chiusura in acciaio INOX.

Proposto nella forma quadrata, in due dimensioni e relative potenze, in due finiture - bianco e antracite - e in due temperature colore, 3000K e 4000K.



IP65 outdoor wall and ceiling LED luminaire. Die-cast aluminium body, painted with polyester powders, highly resistant to UV rays and corrosion: satin tempered glass diffuser.

Reflecting aluminium surface, silicone gasket and inox steel screws.

Available in square shape, in two sizes and related powers, two finishes - white and anthracite - and in two gradations, 3000K and 4000K.



Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
<b>ENT005XX</b>	3000K	1050	8,7W	148 x 148 x 70
<b>ENT006XX</b>	4000K	1120	8,7W	148 x 148 x 70
<b>ENT007XX</b>	3000K	2100	23W	300 x 300 x 70
<b>ENT008XX</b>	4000K	2200	23W	300 x 300 x 70



## Finiture Finishes



B

AN