




# LINK

Faretto LED ad incasso per esterno, da terra, calpestabile (max. 500Kg). Corpo in alluminio con vetro temperato e cassaforma in dotazione. Ghiera e viti di fissaggio in acciaio INOX AISI 304, guarnizioni in silicone per garantire un alto livello di protezione, IP67. Alimentatore LED integrato. Disponibile nella versione tonda e quadrata, due dimensioni e relative potenze e in due temperature colore, 3000K e 4000K. Disponibili giunti certificati IP68 per la realizzazione delle connessioni elettriche, sicure, durevoli e con barriera anticondensa.




LED outdoor recessed luminaire, walk over (max. 500Kg), ground installation. Aluminium body with tempered glass, supplied with recessed box. AISI304 stainless steel ring nut and fixing screws, silicone gasket to ensure a high protection grade, IP67. Integrated LED driver. Available in round and square versions, in two sizes and related powers, in two gradations, 3000K and 4000K. IP68 linear connectors for moisture protection and anti-condensation linear joints are available.



 calpestabile max Kg 500  
walk over max Kg 500




Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
<b>LIN001</b>	3000K	90	1W	Ø67 x 117
<b>LIN005</b>	4000K	100	1W	Ø67 x 117
<b>LIN003</b>	3000K	630	7W	Ø125 x 105
<b>LIN006</b>	4000K	680	7W	Ø125 x 105






LIN001 - LIN005  
LIN002 - LIN007



 calpestabile max Kg 500  
walk over max Kg 500



Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
<b>LIN002</b>	3000K	90	1W	67 x 67 x 117
<b>LIN007</b>	4000K	100	1W	67 x 67 x 117
<b>LIN004</b>	3000K	630	7W	125 x 125 x 105
<b>LIN008</b>	4000K	680	7W	125 x 125 x 105



LIN003 - LIN006  
LIN004 - LIN008

## Finiture Finishes



**Acciaio AISI304** Stainless steel AISI304

## Accessori Accessories



connessione IP68  
IP68 connection

p.945



cassaforma  
inclusa  
recessed box  
included