

# LOOP

Faretto con LED COB ad incasso, estraibile, cardanico, orientabile di 90° rispetto all'asse orizzontale e di 358° rispetto all'asse verticale.


Struttura in alluminio verniciato bianco, diffusore in vetro. Disponibile in tre dimensioni e relative potenze e due temperature colore, 3000K e 4000K. Corredato di alimentatore LED da installare in remoto.

Extractable COB LED downlight, adjustable on two axes can be tilted at 358° on the vertical axis and adjusted 90° on the horizontal axis.



White painted aluminium body, glass diffuser. Available in three sizes and related powers and in two gradations, 3000K and 4000K. Remote LED driver supplied.





Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
LOO101	3000K	1050	10W	Ø110 x 90
LOO102	4000K	1100	10W	Ø110 x 90
LOO103	3000K	2090	20W	Ø130 x 110
LOO104	4000K	2200	20W	Ø130 x 110
LOO105	3000K	3150	30W	Ø165 x 140
LOO106	4000K	3300	30W	Ø165 x 140





foro hole  
Ø 95



foro hole  
Ø 115



foro hole  
Ø 155



## Finiture Finishes



Bianco White