



TORCH


Restyle

Apparecchio LED 48V per esterno IP65, applicabile a terra con apposito picchetto in dotazione. Struttura in acciaio INOX anticorrosione (AISI316) ad elevata resistenza ai raggi ultravioletti e alla corrosione. Alimentatore LED da ordinare separatamente e da installare in remoto. Disponibili giunti certificati IP68 per la realizzazione delle connessioni elettriche con barriera anticondensa.


IP65 outdoor 48V LED floodlight luminaire, suitable for floor mounting with supplied spike. Anti-corrosion and anti-UV (AISI316) stainless steel body. Remote driver as accessory to be ordered separately. IP68 linear connectors for moisture protection and anti-condensation linear joints are available.



Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
TOR001	3000K	230	2,1W	Ø25 x 900



Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
<i>new</i> TOR002	3000K	230	2,1W	Ø64 x 844



Finiture Finishes




Acciaio AISI316 Stainless steel AISI316

Accessori Accessories



connessione IP68
IP68 connection

p.945



TS.807
alimentatore LED
LED driver

p.928