


BAZ

Faretto LED ad incasso RGB, con ottica a 50° installabile a parete o soffitto.
Struttura in ottone cromato con lente in vetro, cavo di alimentazione incluso e può essere installato in ambienti con elevata polvere e umidità (IP44).
Necessita di controller TS.512 settato a 220mA e di alimentatore a 12V per un carico da 1 a 3 faretti, a 24V da 4 a 6 faretti, a 48V da 7 a 13 faretti. Entrambi da installare in remoto.
Cassaforma per installazione in muratura da ordinare come accessorio. Disponibili cavi precablati per connessione rapida da ordinare separatamente.

Ceiling and wall RGB LED downlight, 50° beam angle.
Chrome brass body with glass lens, power cable included and thanks to its (IP44) protection degree it is suitable for installation in damp and dusty environments.
Requires a TS.512 controller set to 220 mA and a power supply at 12 V for a load of 1 to 3 spotlights, 24 V for 4 to 6 spotlights, and 48 V for 7 to 13 spotlights. Both must be installed remotely.
Casting box available as accessory to be ordered separately. Pre-wired cables for quick connection are available as accessories to be ordered separately.



Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
8856	RGB	110	2W - 220mA	Ø40 x 45



MT.8856-1

cavo 3 poli (Rosso-Verde-Blu) precablato con 1 connettore maschio - L:1,5 m
pre-wired 3-pole cable (Red-Green-Blue) with 1 plug connector - L:1,5 m

MT.8856-2

cavo 3 poli (Rosso-Verde-Blu) precablato con 2 connettori maschio - L:1,5 m
pre-wired 3-pole cable (Red-Green-Blue) with 2 plug connectors - L:1,5 m

MT.8856-3

cavo 3 poli (Arancio-Bianco-Nero) precablato con 1 connettore maschio - L:1,5 m
pre-wired 3-pole cable (Orange-White-Black) with 1 plug connector - L:1,5 m

Finiture Finishes



Ottone cromato Chrome brass


Accessori Accessories



TS.512
telecomando + dimmer controller
radio-frequency remote + dimmer controller



MT.8856
cassaforma per muratura
casting box
Ø60 x 69



alimentatore 12V
12V driver

p.931