



Poliedrico.
Multi-faceted.

SILVER



Apparecchio LED a parete per esterno IP65 monoemissione e biemissione. Struttura in pressofusione di alluminio verniciato con polveri poliestere a elevata resistenza ai raggi ultravioletti e alla corrosione, diffusore in vetro temperato. Guarnizioni in silicone e viti di chiusura in acciaio INOX.

Disponibile in forma quadrata e stondata, in tre finiture - grigio, antracite e marrone - e in due temperature colore, 3000K e 4000K.

IP65 outdoor wall LED luminaire with direct or direct/indirect light emission. Die-cast aluminium body painted with polyester powders, highly resistant to UV rays and corrosion, tempered glass diffuser.

Silicone gasket and INOX steel screws. Available in round and square shape, in three finishes - grey, anthracite and brown - and in two gradations, 3000K and 4000K.





SILVER

MONOEMISSIONE DIRECT LIGHT





| Codice Code | CCT | Flusso lm Flux lm | Potenza Wattage | Dimensioni mm Dimensions mm |
|-----------------------|-------|----------------------|--------------------|--------------------------------|
| A.122-XX-LED-C | 3000K | 420 | 1x4,5W | 100 x 100 x 110 |
| A.122-XX-LED-F | 4000K | 505 | 1x4,5W | 100 x 100 x 110 |



BIEMISSIONE DIRECT-INDIRECT LIGHT





| Codice Code | CCT | Flusso lm Flux lm | Potenza Wattage | Dimensioni mm Dimensions mm |
|-----------------------|-------|----------------------|--------------------|--------------------------------|
| A.124-XX-LED-C | 3000K | 420+420 | 2x4,5W | 100 x 100 x 110 |
| A.124-XX-LED-F | 4000K | 505+505 | 2x4,5W | 100 x 100 x 110 |



MONOEMISSIONE DIRECT LIGHT





| Codice Code | CCT | Flusso lm Flux lm | Potenza Wattage | Dimensioni mm Dimensions mm |
|-----------------------|-------|----------------------|--------------------|--------------------------------|
| A.129-XX-LED-C | 3000K | 420 | 1x4,5W | 96 x 96 x 112 |
| A.129-XX-LED-F | 4000K | 505 | 1x4,5W | 96 x 96 x 112 |



BIEMISSIONE DIRECT-INDIRECT LIGHT



| Codice Code | CCT | Flusso lm Flux lm | Potenza Wattage | Dimensioni mm Dimensions mm |
|-----------------------|-------|----------------------|--------------------|--------------------------------|
| A.130-XX-LED-C | 3000K | 420+420 | 2x4,5W | 96 x 96 x 112 |
| A.130-XX-LED-F | 4000K | 505+505 | 2x4,5W | 96 x 96 x 112 |



Finiture Anello Ring Finishes



B



AN



MA

Accessori Accessories



Optica da 40° disponibili su richiesta
40° optic available on request

DARK SKY
con luce diretta verso il basso, per codice:
with direct emission, for code:

A.122-XX-LED-C
A.129-XX-LED-C