



Apparecchio a parete per esterno IP44 con attacco GU10, che consente di montare lampadina LED.

Struttura in pressofusione di alluminio verniciato con polveri poliestere a elevata resistenza ai raggi ultravioletti e alla corrosione, diffusore in vetro temperato.

Disponibile in versione monoemissione o biemissione, proposte in due finiture, grigio e nero.

La versione monoemissione può essere montata con fascio di luce verso il basso o verso l'alto.

IP44 outdoor wall luminaire with GU10 lamp holder that allows mounting the LED lamp.

Die-cast aluminium body, painted with polyester powders, highly resistant to UV rays and corrosion, tempered glass diffuser.

Available with direct or direct-indirect light emission, available in two finishes, grey and black.


The direct light emission version can be mounted with direct or indirect light emission.


APOLLO



MONOEMISSIONE DIRECT LIGHT





Codice Code		Potenza Wattage	Dimensioni mm Dimensions mm
APO001XX	GU10	1x50W max	Ø76 x 103 x 126



BIEMISSIONE DIRECT-INDIRECT LIGHT



Codice Code		Potenza Wattage	Dimensioni mm Dimensions mm
APO002XX	GU10	2x50W max	Ø76 x 196 x 126



Finiture Finishes



GR



N