



# AVERY





Apparecchio LED a parete per esterno IP65, monoemissione e biemissione, tondo o quadrato.

Struttura in pressofusione di alluminio e diffusore in vetro temperato. Disponibile in tre finiture - antracite, grigio e marrone - e in due temperature colore, 3000K e 4000K.

Disponibili giunti certificati IP68 per la realizzazione delle connessioni elettriche, sicure, durevoli e con barriera anticondensa.

IP65 outdoor wall LED luminaire with direct or direct/indirect light emission, with round or square shape.

Die-cast aluminium body and tempered glass diffuser. Available in three finishes - anthracite, grey and brown - and in two gradations, 3000K and 4000K.



IP68 linear connectors for moisture protection and anti-condensation linear joints are available.

# AVERY

## MONOEMISSIONE DIRECT LIGHT





Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
<b>AVE007XX</b>	3000K	2520	15,6W	Ø130 x 250 x 190
<b>AVE008XX</b>	4000K	2620	15,6W	Ø130 x 250 x 190



## BIEMISSIONE DIRECT-INDIRECT LIGHT





Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
<b>AVE005XX</b>	3000K	2520+2520	2x15,6W	Ø130 x 250 x 190
<b>AVE006XX</b>	4000K	2620+2620	2x15,6W	Ø130 x 250 x 190



## MONOEMISSIONE DIRECT LIGHT





Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
<b>AVE003XX</b>	3000K	2520	15,6W	130 x 220 x 200
<b>AVE004XX</b>	4000K	2620	15,6W	130 x 220 x 200



## BIEMISSIONE DIRECT-INDIRECT LIGHT



Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
<b>AVE001XX</b>	3000K	2520+2520	2x15,6W	130 x 220 x 200
<b>AVE002XX</b>	4000K	2620+2620	2x15,6W	130 x 220 x 200



### Finiture Finishes



GR

AN

MA

### Accessori Accessories



connessione IP68  
IP68 connection

p.945



Ottiche da 16° e 74° disponibili su  
richiesta  
16° and 74° optics available on  
request