

Presentazione

Product	Single Throw Safety Switch
Current Rating	600 A
Number of Poles	3
Voltage Rating	600 V AC/DC
Wire Size	AWG 3/0...500 kcmil copper or aluminium
Disconnect Type	Sconnessione fusibile
Mounting Type	Parete
Factory Installed Neutral	None
Duty Rating	Heavy duty
Certifications	UL listed file E2875
Enclosure Rating	NEMA 3R/12

Caratteristiche tecniche

Potenza motore in hp	150 Hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 240.6 400 Hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 200 Hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 240.6 500 Hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 50 Hp a 250 VDC 50 hp at 600 V DC
Larghezza	666,75 mm
Altezza	1174,75 mm
Profondità	257,30 mm
Coppia di serraggio	42.37 N.m (AWG 3/0...500 kcmil)

Confezionamenti

Peso imballo (Kg)	79,832 kg
-------------------	-----------

Sostenibilità dell'offerta

Stato offerta sostenibile	Prodotto Green Premium
Regolamento REACh	 Dichiarazione REACh
REACh senza SVHC	Sì
Direttiva RoHS UE	Conformità  EU RoHS Dichiarazione
Senza mercurio	Sì
Informazioni esenzioni RoHS	 Sì
Regolamento RoHS della Cina	 Dichiarazione RoHS Della Cina
Informazioni ambientali	 Profilo Ambientale Del Prodotto
Senza PVC	Sì
Contenuto di alogeni	Prodotto con parti in plastica prive di alogeni

Garanzia contrattuale

Garanzia	18 mesi
----------	---------